

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.																				
TERMINAL ROUTES										MISSED APPROACH																				
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: PTT NDB																			
ANY VORTAC			PTT NDB			314.17 / 43.75			5500		CLIMBING LEFT TURN TO 3600 IN PTT NDB HOLDING PATTERN.																			
DDC VORTAC			PTT NDB			088.71 / 60.32			6500																					
HUT VOR/DME			PTT NDB			243.47 / 41.89			3800																					
THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 17-23.										ADDITIONAL FLIGHT DATA: HOLD N, LT, 172.87 INBOUND. CHART FAS OBST: 2079 100 FT TREE 374318N/0984609W. FAC ALIGNED TO FACILITY FAC CROSSES RWY C/L EXTENDED 5899 FT FROM THLD.																				
1. PT <u>R</u> SIDE OF COURSE <u>352.87</u> OUTBOUND <u>3600</u> FT WITHIN <u>10</u> MILES OF <u>PTT NDB</u> (IAF)										MAG VAR: 7E EPOCH YEAR: 1990																				
2. _____																														
3. FAC <u>172.87</u> FAF _____ DIST FAF TO MAP _____ THLD _____																														
4. MIN. ALT _____																														
8. MSA FROM: PTT NDB 3800																														
MINIMUMS																														
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD																		
CATEGORY =====>		A			B			C			D			E																
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA															
S-17	2440	1 1/4	488	2440	1 1/4	488	2440	1 1/4	488		NA																			
CIRCLING	2440	1 1/4	487	2440	1 1/4	487	2440	1 1/2	487		NA																			
NOTES:																														
<div>QUALITY 32 CHECKED</div>																														
																CITY AND STATE PRATT, KS			ELEVATION: 1953 TDZE: 1952 AIRPORT NAME: PRATT RGNL			FACILITY IDENTIFIER: PTT			PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 17, AMDT 5A, 12/07/2017				SUP	
																AMDT 5				DATE 05/15/2003										

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
32
CHECKED

CITY AND STATE

PRATT, KS

ELEVATION: 1953

TDZE: 1952

AIRPORT NAME:

PRATT RGNL

FACILITY
IDENTIFIER:

PTT

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

NDB RWY 17, AMDT 5A, 12/07/2017

SUP:

AMDT: 5

DATED: 05/15/2003