

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 4.61 NM AFTER WELIN OR AT ICT 26.61 DME						
ICT VORTAC (IAF)		VEUCUD/16.00 DME		152.42 / 16.00				3100		CLIMBING RIGHT TURN TO 3300 ON HEADING 290 AND HUT VOR/DME R-149 TO REKOC/HUT 26.00 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 149.47 INBOUND. CHART FAS OBST: 1559 TOWER 372200N/0972413W CHART ICT R-057 AT KUDPY. CHART ICT R-249 AT KUHCU. WELIN TO RW17: 3.03/40.						
KUDPY/16.00 DME CW (IAF)		VEUCUD/16.00 DME		16.00 DME ARC				3100								
KUHCU/16.00 DME CCW (IAF)		VEUCUD/16.00 DME		16.00 DME ARC				3100								
VEUCUD/16.00 DME (IF)		KOPNE/20.00 DME		152.42 / 4.00 (ICT R-152)				2900								
KOPNE/20.00 DME		WELIN/ICT 22.00 DME		152.42 / 2.00 (ICT R-152)				2800								
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT ICT VORTAC 3. FAC 152.42 FAF WELIN/ICT 22.00 DME DIST FAF TO MAP _____ THLD 4.61 4. MIN. ALT ICT VORTAC 3600, VEUCUD 3100, KOPNE 2900, WELIN 2800 8. MSA FROM: ICT VORTAC 360-270 3600, 270-360 4100 (28 NM)										MAG VAR: 7E				EPOCH YEAR: 1985		
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		X						
CATEGORY =====>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-17	2100	1	823	2100	1 1/4	823	2100	2 1/2	823	2100	2 3/4	823				
CIRCLING	2100	1	823	2100	1 1/4	823	2100	2 1/2	823	2100	2 3/4	823				
WICHITA DWIGHT D EISENHOWER NATIONAL ALTIMETER SETTING MINIMUMS																
S-17	2160	1 1/4	883	2160	1 1/4	883	2160	2 3/4	883	2160	3	883				
CIRCLING	2160	1 1/4	883	2160	1 1/4	883	2160	2 3/4	883	2160	3	883				
NOTES: CHART NOTE: DME REQUIRED. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON ICT VORTAC AIRWAY RADIALS 130 CW 212. CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE WICHITA DWIGHT D EISENHOWER NATIONAL ALTIMETER SETTING.																
CITY AND STATE		ELEVATION: 1277		TDZE: 1277		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP VOR/DME RWY 17				
WELLINGTON, KS		AIRPORT NAME:		WELLINGTON MUNI		ICT		VOR RWY 17, AMDT 2B 7 DECEMBER 2017				AMDT 2A				
												DATE 09/25/2008				

