

U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE												
BONEE WP (IAF)	IMOSE WP (TF) (FB) (NO PT)	338.34/10.92	2800	LNAV: RW26											
ROD VORTAC (IAF)	IMOSE WP (TF) (FB) (NO PT)	195.48/4.50	2800												
IMOSE WP (IF/IAF)	ZALAD WP (TF) (FB)	261.68/6.56	2600	CLIMB TO 2600 DIRECT MANUE WP AND HOLD											
RW26 (MAP)	1380 MSL (CA)	261.60													
1380 MSL	MANUE (DF) (FO)		2600	ADDITIONAL FLIGHT DATA: HOLD W, RT, 081.36 INBOUND FAS OBST: 1130 TOWER 400934/841412 CHART: 1114 TREE 401009/841121 ZALAD WP TO RW26: 3.00/40 FINAL SEGMENT (TF)											
PROCEDURE NA FOR ARRIVAL	AT BONEE ON V12 EAST BOUND	AND FOR ARRIVAL AT ROD													
VORTAC ON AIRWAY RADIALS	207 CW 273														
1. PT <u>NA</u> SIDE OF COURSE <u>OUTBOUND</u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)				MAG VAR: 6W EPOCH YEAR: 05											
2. <u>HOLD E</u> IMOSE WP, RT, 261.68 INBOUND, 2800 FT IN LIEU OF PT (IAF)															
3. FAC: <u>261.60</u> FAF: <u>ZALAD WP</u> DIST FAF TO MAP: <u>4.94</u> THLD: <u>4.94</u>															
4. MIN. ALT: <u>IMOSE WP 2800, ZALAD WP 2600</u>															
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>															
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>															
7. GS ANGLE: <u> </u> TCH: <u>34:1 IS CLEAR</u>															
8. MSA FROM: <u>RW26 3100</u>															
MINIMUMS															
TAKEOFF:	<input checked="" type="checkbox"/> STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT		ALTERNATE: N A		<input checked="" type="checkbox"/>									
CATEGORY \Rightarrow	A			B			C			D			E		
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	1380	1	386	1380	1	386	1380	1	386	1380	1 1/4	386			
CIRCLING	1440	1	446	1460	1	466	1460	1 1/2	466	1560	2	566			
NOTES: USE DAYTON INTERNATIONAL ALTIMETER SETTING. GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA.															
CITY AND STATE		ELEVATION: 994 TDZE: 994		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP:					
PIQUA, OH		AIRPORT NAME: PIQUA AIRPORT-HARTZELL FIELD		RNAV		JUN 10 2004 RNAV (GPS) RWY 26, ORIG				AMDT: NONE					
										DATE					