

U.S. Department of Transportation Federal Aviation Administration		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES				MISSED APPROACH								
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW08 CLIMB TO 2600 DIRECT IMOSE WP AND HOLD ADDITIONAL FLIGHT DATA: HOLD E, RT, 261.68 INBOUND FAS OBST: 1099 TREE 400933/841927 CHART 1381 TOWER 400721/842358 TABOE WP TO RW08: 3.00/40 FINAL SEGMENT (TF)								
RID VORTAC	OKONE WP (TF) (FB)	058.43/19.58	2700									
OKONE WP (IAF)	MANUE WP (TF) (FB) (NO PT)	351.40/10.00	2600									
ROSSY WP (IAF)	MANUE WP (TF) (FB) (NO PT)	173.48/9.44	2600									
MANUE WP (IF/IAF)	TABOE WP (TF) (FB)	081.36/6.58	2600									
RW08 (MAP)	1400 MSL (CA)	081.45										
1400 MSL	IMOSE WP (DF) (FO)		2600									
PROCEDURE NA FOR ARRIVAL VORTAC VIA V12-517 SOUTH	AT ROSSY ON V55 NORTHWEST WESTBOUND	BOUND, AND ARRIVAL AT RID										
1. PT NA SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W MANUE WP, RT, 081.36 INBOUND, 2600 FT IN LIEU OF PT (IAF) 3. FAC: 081.45 FAF: TABOE WP DIST FAF TO MAP: 4.92 THLD: 4.92 4. MIN. ALT: MANUE WP 2600, TABOE WP 2600 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS CLEAR 8. MSA FROM: RW08 3100				MAG VAR: 6W EPOCH YEAR: 05								
MINIMUMS												
TAKEOFF:	<input checked="" type="checkbox"/> STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT		ALTERNATE: N A		<input checked="" type="checkbox"/>						
CATEGORY ==>	A		B		C		D		E			
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	1400	1	406	1400	1	406	1400	1 1/4	406	1400	1 1/4	406
CIRCLING	1440	1	446	1460	1	466	1460	1 1/2	466	1560	2	566
NOTES: USE DAYTON INTERNATIONAL ALTIMETER SETTING. GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA.												
CITY AND STATE		ELEVATION: 994 TDZE: 994		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:			SUP:			
PIQUA, OH		AIRPORT NAME: PIQUA AIRPORT-HARTZELL FIELD		RNAV		JUN 10 2004 RNAV (GPS) RWY 8, ORIG			AMDT: NONE			
									DATE			