

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: VHP 14.43 DME FIX
VHP VORTAC	ZUTID/19.79 DME	020.74 / 19.79	2700	CLIMB TO 2700 DIRECT VHP VORTAC AND HOLD.
OKK VORTAC (IAF)	YUKUL/VHP 29.79 DME (NOPT)	191.89 / 15.43	2700	
YUKUL/29.79 DME (IF)	ZUTID/19.79 DME	200.74 / 10.00 (VHP R-021)	2700	
				ADDITIONAL FLIGHT DATA: HOLD S, LT, 022.00 INBOUND. CHART FAS OBST: 1069 TREE 400425N/0861444W CHART 1169 TOWER 400829N/0861429W. VUVUY TO RW18: 3.07/45 1136 AAO 400409N/0861130W

1. PT R SIDE OF COURSE 020.74 OUTBOUND 2700 FT WITHIN 10 MILES OF ZUTID (IAF)
 2.
 3. FAC 200.74 FAF ZUTID/19.79 DME DIST FAF TO MAP THLD 5.36
 4. MIN. ALT ZUTID 2700, VUVUY/16.68 DME 1620
 8. MSA FROM: VHP VORTAC 3100

MAG VAR: 1E EPOCH YEAR: 1965

MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @							
CATEGORY ==>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-18	1320	1	398	1320	1	398	1320	1 1/8	398	1320	1 1/8	398				
CIRCLING	1360	1	438	1380	1	458	1380	1 1/2	458	1480	2	558				

NOTES:

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE INDIANAPOLIS INTL ALTIMETER SETTING AND INCREASE ALL MDA 80 FT AND S-18 CATS C/D VISIBILITY 1/4 MILE.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT OKK VORTAC ON V305 NORTHBOUND.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
CHECKED

CITY AND STATE INDIANAPOLIS, IN	ELEVATION: 922 AIRPORT NAME: INDIANAPOLIS EXECUTIVE	THRE: 922 FACILITY IDENTIFIER: VHP	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 18, AMDT 1 5 May 2011	SUP
				AMDT ORIG
				DATE 09/25/2008

711-7 Pub 5/5/11

ALL AFFECTED PROCEDURES REVIEWED? <input type="checkbox"/> YES <input type="checkbox"/> NO		COORDINATES OF FACILITIES		REQUIRED EFFECTIVE DATE	
COORDINATED WITH:					
ATA <input type="checkbox"/>	AAT <input type="checkbox"/>	ALPA <input type="checkbox"/>	APA <input type="checkbox"/>	AOPA <input type="checkbox"/>	NBAA <input type="checkbox"/>
OTHER (specify) _____					
FLIGHT CHECKED BY					
NAME:				FIFO	DATE:
DEVELOPED BY					
NAME:				FIFO	DATE:
APPROVED BY					
NAME:				FIFO	DATE:
CHANGES: CHANGES CONT. RECEIVED, USE INDIANAPOLIS INTL ALTIMETER SETTING: INCREASE DA 62 FT AND VISIBILITY ALL CATS 1/8 MILE; INCREASE ALL MDA 80 FT, AND LNAV VISIBILITY CAT C/D 1/4 MILE. 14. ADDED PROCEDURE NA FOR ARRIVALS AT CLANG VIA V14-192-210 SOUTHWEST BOUND. 15. ADDED ALTERNATE MINIMUMS. 16. DELETED VDA.					
REASONS:					

QUALITY
CHECKED