

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW22 CLIMB TO 3100 DIRECT AXUXE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 042.91 INBOUND. CHART FAS OBST: 1235 BLDG 385259N/0944912W DISTANCE TO THLD FROM 250 HAT: 0.61 NM. CHART VDP AT 1.28 NM TO RW22* *LNAV ONLY. WAAS CHANNEL # 45739 REFERENCE PATH ID: W22A CHART CIRCLING ICON CHART 1332 TOWER 385248N/0944727W LTP HAE: 299.4 M					
AYOBU (IAF)		FALOV (NOPT) (FB)		133.10 / 7.00				3100							
SIPSE (IAF)		FALOV (NOPT) (FB)		313.22 / 7.00				3100							
FALOV (IF/IAF)		CALVU (FB)		223.16 / 7.47				2700							
CALVU (FAF)		RW22 (MAP) (FO)		223.09 / 4.92											
RW22 (MAP)		1337 MSL		223.09											
1337 MSL		AXUXE (FO)						3100							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NE FALOV, RT, 223.16 INBOUND, 3100 FT. IN LIEU OF PT (IAF) 3. FAC: 223.09 FAF: CALVU DIST FAF TO MAP: 4.92 THLD: 4.92 4. MIN. ALT: FALOV 3100, CALVU 2700 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2700 GS ALT AT: CALVU 2700 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS CLEAR 8. MSA FROM: RW22 3100										MAG VAR: 4E		EPOCH YEAR: 2000			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1337	1	250	1337	1	250	1337	1	250	1337	1	250			
LNAV/VNAV DA	1350	1	263	1350	1	263	1350	1	263	1350	1	263			
LNAV MDA	1540	1	453	1540	1	453	1540	1 3/8	453	1540	1 3/8	453			
CIRCLING	1560	1	473	1560	1	473	1580	1 1/2	493	1640	2	553			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (-2F) OR ABOVE 54C (130F). @ NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING JOHNSON COUNTY EXECUTIVE ALTIMETER SETTING. CHART NOTE: DME/DME RNP-0.3 NA. (CONTINUED ON PAGE 2)															
CITY AND STATE			ELEVATION: 1087 TDZE: 1087			FACILITY IDENTIFIER:			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:		
OLATHE, KS			AIRPORT NAME:			RNAV			RNAV (GPS) RWY 22, ORIG 15 SEPTEMBER 2016				AMDT: NONE		
			NEW CENTURY AIRCENTER										DATED:		



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: RADAR REQUIRED.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JOHNSON COUNTY EXECUTIVE ALTIMETER SETTING: INCREASE LPV DA TO 1355 FEET AND LNAV/VNAV DA TO 1368 FEET AND ALL MDA 20 FEET.

QUALITY
25
CHECKED

CITY AND STATE

OLATHE, KS

ELEVATION: 1087

TDZE: 1087

AIRPORT NAME:

NEW CENTURY AIRCENTER

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 22, ORIG
15 SEPTEMBER 2016

SUP:

AMDT: **NONE**

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KIXD
RUNWAY	RW22
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W22A
LTP/FTP LATITUDE	385016.1185N
LTP/FTP LONGITUDE	0945254.7780W
LTP/FTP ELLIPSOIDAL HEIGHT	+02994
FPAP LATITUDE	384915.3315N
FPAP LONGITUDE	0945418.2110W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1184
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

826F711E

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+03314
FPAP ORTHOMETRIC HEIGHT	+03314

QUALITY
25
CHECKED

CITY AND STATE OLATHE, KS	ELEVATION: 1087 AIRPORT NAME: NEW CENTURY AIRCENTER	TDZE: 1087 	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, ORIG 15 SEPTEMBER 2016	SUP:
					AMDT: NONE
					DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - KIXD

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
AYOBU	010	AYOBU	IF	FB										E A
AYOBU	020	FALOV	TF	FB	1.0	133.1						AA 03100		EE B
FALOV	010	FALOV	HF	FO		223.2			R			AA 03100		EE A
SIPSE	010	SIPSE	IF	FB										E A
SIPSE	020	FALOV	TF	FB	1.0	313.2						AA 03100		EE B
	010	FALOV	IF	FB								AA 03100		E I
	020	CALVU	TF	FB	1.0	223.2				RW22		AA 02700		E F
	030	RW22	TF	FO	0.3	223.1		3.00				AT 01132		GY M
	040		CA	FB		223.1						AA 01337		M
	050	AXUXE	DF	FO								AA 03100		EY
	060	AXUXE	HM	FO		042.9			R			AA 03100		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
AXUXE	N384110.48	W0950521.41
AYOBU	N390350.74	W0944723.78
CALVU	N385337.52	W0944817.90
FALOV	N385842.64	W0944117.12
SIPSE	N385334.22	W0943511.34

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW22	N385016.12	W0945254.78	01087	45

QUALITY
25
CHECKED

CITY AND STATE OLATHE, KS	ELEVATION: 1087 TDZE: 1087	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 22, ORIG 15 SEPTEMBER 2016	SUP:
	AIRPORT NAME: NEW CENTURY AIRCENTER			AMDT: NONE
				DATED: