

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97. 27										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH											
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: UOT NDB										
GRD VORTAC			UOT NDB			045.28 / 36.27			2500		CLIMB TO 1700 THEN CLIMBING RIGHT TURN TO 2500 DIRECT UOT NDB AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 061.44 INBOUND. FAS OBST: 891 TOWER 343646/814250. FAC CROSSES RWY C/L EXTENDED 3003 FROM THLD. MIRL RWY 5-23. VASI RWY 5 AND 23.										
BUILD INT			UOT NDB			149.07 / 10.16			2500												
ADENA INT			UOT NDB			245.17 / 5.73			2500												
WILLS INT			UOT NDB			338.54 / 12.73			2500												
1. PT <u> L </u> SIDE OF COURSE <u> 241.44 </u> OUTBOUND <u> 2500 </u> FT WITHIN <u> 10 </u> MILES OF <u> UOT NDB </u> (IAF) 2. _____ 3. FAC <u>061.44</u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT _____ 8. MSA FROM: <u>UOT NDB 3000</u>										MAG VAR: 6W EPOCH YEAR: 00											
MINIMUMS																					
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15 FOR THIS AIRPORT						ALTERNATE:		N A		X					
CATEGORY		A			B			C			D			E							
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA					
S-5		1420	1	815	1420	1 1/4	815		NA			NA									
CIRCLING		1420	1	815	1420	1 1/4	815		NA			NA									
NOTES: USE GREER ALTIMETER SETTING.																					
CITY AND STATE				ELEVATION: 605 TDZE: 605				FACILITY IDENTIFIER:				PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP					
UNION, SC				UNION COUNTY, TROY SHELTON FIELD				UOT				NDB RWY 5, ORIG				AMDT NONE					
																DATED					