

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES														MISSED APPROACH							
FROM				TO			COURSE AND DISTANCE				ALTITUDE		LNAV: RW06L								
BARWU (IF/IAF)				AGOMY (FB)			054.44 / 9.62				1700		CLIMBING RIGHT TURN TO 3000 DIRECT BARWU AND HOLD.								
AGOMY (FAF)				RW06L (MAP) (FO)			054.52 / 4.99														
RW06L (MAP)				446 MSL			054.52														
446 MSL				BARWU (FO)							3000		ADDITIONAL FLIGHT DATA: CHART FAS OBST: 297 TOWER 315102N/0813603W CHART CIRCLING ICON. CHART R-3005B, C, D, E. CHART R-3007C, D. AGOMY TO RW06L: 3.04/46								
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																					
2. HOLD SW BARWU, RT, 054.44 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																					
3. FAC: 054.52 FAF: AGOMY _____ DIST FAF TO MAP: 4.99 THLD: 4.99																					
4. MIN. ALT: BARWU 3000, AGOMY 1700																					
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																					
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																					
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR																					
8. MSA FROM: RW06L 2600														MAG VAR: 4W				EPOCH YEAR: 1985			
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A			STANDARD @											
CATEGORY ==>		A			B			C			D			E							
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA						
LNAV MDA	600	1	554	600	1	554	600	1 1/4	554	600	1 1/4	554									
CIRCLING	600	1	554	620	1	574	660	1 3/4	614	680	2	634									
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SAVANNAH/HILTON HEAD INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, LNAV CAT C AND D VISIBILITY 1/4 MILE, AND CIRCLING CAT C VISIBILITY 1/4 MILE. (SEE FORM 8260-10)																					
CITY AND STATE FORT STEWART(HINESVILLE), GA				ELEVATION: 46 TDZE: 46 AIRPORT NAME: WRIGHT AAF (FORT STEWART)/MIDCOAST RGNL				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 6L, ORIG-B 5 FEBRUARY 2015				SUP: AMDT: ORIG-A DATED 04/03/2014							

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: CIRCLING NA NE OF RWY 15L/33R.

CHART PLANVIEW NOTE: NOPT FOR ARRIVAL AT BARWU ON V578 EASTBOUND.

CHART NOTE: NIGHT LANDING: RWY 6L, 6R NA.

CHART PLANVIEW NOTE: RADAR REQUIRED.

CHART NOTE: PROCEDURE NA WHEN R3005C/D IS ACTIVE AND LHW TOWER IS CLOSED.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

QUALITY
9
CHECKED


CITY AND STATE FORT STEWART(HINESVILLE), GA	ELEVATION: 46 AIRPORT NAME: WRIGHT AAF (FORT STEWART)/MIDCOAST RGNL	TDZE: 46	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 6L, ORIG-B 5 FEBRUARY 2015	SUP:
					AMDT: ORIG-A
					DATED: 04/03/2014

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
4
CHECKED

Page 3 of 4 Pages

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - FAR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	BARWU	BARWU	010	IAF	HF	R	FO		054.4 (050.4T)	004.0	AA 03000	
		BARWU	010	FACF	IF		FB				AA 03000	
		AGOMY	020	FAF	TF		FB	0.5	054.4 (050.4T)	009.6	AA 01700	
		RW06L	030	MAP	TF		FO	0.3	054.5 (050.5T)	005.0	AT 00089	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		054.5 (050.5T)		AA 00446	
		BARWU	050		DF	R	FO				AA 03000	
		BARWU	060		HM	R	FO		054.4 (050.4T)	004.0	AA 03000	
POINT DATA		WAYPOINT			LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS	
		AGOMY			N314952.44		W0813848.08		N3149.874		W08138.801	
		BARWU			N314344.21		W0814730.68		N3143.737		W08147.511	
		RW06L			N315303.29		W0813416.38		N3153.055		W08134.273	
RUNWAY DATA				THRESHOLD								
		RWY		ELEVATION		TCH						
		RW06L	00043			46						



CITY AND STATE FORT STEWART(HINESVILLE), GA	ELEVATION: 46	TDZE: 46	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: WRIGHT AAF (FORT STEWART)/MIDCOAST		RNAV	RNAV (GPS) RWY 6L, ORIG-B 5 FEBRUARY 2015	AMDT: ORIG-A
	RGNL				DATED: 04/03/2014