

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Cellings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH											
FROM		TO			COURSE AND DISTANCE					ALTITUDE		MAP: 2.33 MILES AFTER ENA VOR/DME OR AT ENA 2.33 DME FIX CLIMB TO 2200 ON ENA VOR/DME R-192 TO DIXIT INT/ENA 10.00 DME AND HOLD.									
SWANS/ENA 10.00 DME (IAF)		TBONE/ENA 8.00 DME (NOPT)			277.00 / 2.73 (HDG) & 192.11 / 1.39 (ENA R-012)					2000		ADDITIONAL FLIGHT DATA: HOLD S, LT, 012.08 INBOUND. CHART FAS OBST: 252 TOWER 603555N/1511240W CHART VDP AT 1.17 DME; DISTANCE VDP TO THLD 1.16 MILES. CHART (CUXET) AT INTERSECTION OF SWANS DR LEG AND INTERMEDIATE COURSE. CHART ENA R-095 AT ROJAR. CHART ENA R-266 AT TWIGI. ENA VOR/DME TO RW19R: 3.44/51.									
ROJAR/ENA 8.00 DME CCW (IAF)		TBONE/ENA 8.00 DME (NOPT)			8.00 DME ARC (ENA LR-027)					2000											
TWIGI/ENA 8.00 DME CW (IAF)		TBONE/ENA 8.00 DME (NOPT)			8.00 DME ARC (ENA LR-357)					2000											
TBONE/ENA 8.00 DME (IF)		FATEL INT/ENA 2.50 DME			192.10 / 5.50 (ENA R-012)					1300											
FATEL INT/ENA 2.50 DME		ENA VOR/DME			192.10 / 2.50					1000											
1. PT <u>L</u> SIDE OF COURSE <u>012.07</u> OUTBOUND <u>2000</u> FT WITHIN <u>10</u> MILES OF <u>ENA VOR/DME</u> (IAF) 2. _____ 3. FAC <u>192.07</u> FAF <u>ENA VOR/DME</u> DIST FAF TO MAP <u>2.33</u> THLD <u>2.33</u> 4. MIN. ALT <u>FATEL 1300, ENA VOR/DME 1000</u> 8. MSA FROM: <u>ENA VOR/DME 030-210 3500, 210-030 2200</u>										MAG VAR: 19E EPOCH YEAR: 2010											
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A			B			C			D			E							
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA					
S-19R		520	2400	422	520	2400	422	520	4000	422	520	4000	422								
CIRCLING		560	1	461	580	1	481	580	1 1/2	481	660	2	561								
NOTES: CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: ADF OR DME REQUIRED. CHART NOTE: VDP NA WHEN USING SOLDOTNA ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SOLDOTNA ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET, INCREASE S-19R CATS C AND D VISIBILITY TO 1 MILE.																	@ NA WHEN LOCAL WEATHER NOT AVAILABLE.				
CITY AND STATE		ELEVATION: 99			THRE: 98			FACILITY IDENTIFIER:			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP							
KENAI, AK		AIRPORT NAME:			KENAI MUNI			ENA			VOR RWY 19R, AMDT 19, 9 FEB 2012			AMDT 18C							
														DATE 10/22/2009							