

<b>US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION</b>				<b>RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		<b>RNP: DA</b>  CLIMB TO 4000 ON TRACK 200.11 TO BOSGE AND LEFT TURN TO AKIKE AND ON TRACK 029.77 TO KRNKL AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD E, RT, 289.67 INBOUND. DISTANCE TO THLD FROM 324 HAT: 0.84 NM. ROUTE TYPE QUALIFIER 1: F ROUTE TYPE QUALIFIER 2: S ROUTE TYPE: A, H #TCH 494.7 MSL (DO NOT CHART) CHART BETWEEN 5000 AND 6500 AT MINRR CHART BETWEEN 5000 AND 6500 AT ROAAD CHART: DELTA 1 MOA					
MUSHR (IAF)		TRPLN (TF) (FB) (RNP 1.00)		154.91 / 4.51				5500							
TRPLN (IF)		CIGNI (TF) (FB) (RNP 0.40)		178.98 / 8.69				3300							
CIGNI		WUNDU (TF) (FB) (RNP 0.30)		200.28 / 3.64				2200							
WUNDU		JOGUP (TF) (FB) (RNP 0.30)		200.20 / 1.70				1700							
ROAAD (IAF)		JUSIV (TF) (FB) (RNP 1.00)		336.01 / 3.89				5000							
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT WUNDU 3. FAC: <u>200.16</u> FAF: _____ DIST FAF TO MAP: _____ THLD: _____ 4. MIN. ALT: <b>WUNDU 2200, JOGUP 1700</b> 5. DIST TO THLD FROM OM: <u>3.78</u> MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: <u>1700</u> GS ALT AT: <b>JOGUP 1700</b> OM: _____ MM: _____ IM: _____ 7. GS ANGLE: <u>3.00</u> TCH: <u>55.8</u> # <u>34:1</u> IS CLEAR 8. MSA FROM: <b>RW20R 4500</b>															
										MAG VAR: 18E			EPOCH YEAR: 2020		
<b>MINIMUMS</b>															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		<b>STANDARD</b>					
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
<b>AUTHORIZATION REQUIRED</b>															
RNP 0.10 DA	763	3000	324	763	3000	324	763	3000	324	763	3000	324			
RNP 0.30 DA	922	6000	483	922	6000	483	922	6000	483	922	6000	483			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -18C (0F) OR ABOVE 54C (130F). CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: RF AND GPS REQUIRED. (CONTINUED ON PAGE 2)															
CITY AND STATE		ELEVATION: 439 TDZE: 439				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:			
FAIRBANKS, AK		AIRPORT NAME: FAIRBANKS INTL				RNAV		RNAV (RNP) Z RWY 20R, AMDT 1 22 JUNE 2017				AMDT: ORIG-A			
												DATED 11/13/2014			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33					
TERMINAL ROUTES, (CONT.):					
FROM		TO	COURSE AND DISTANCE	ALTITUDE	
JUSIV (IF)	IMHID (TF) (FB) (RNP 0.50)		339.09 / 3.46	4200	
IMHID	OMPUE (RF) (FB) (RNP 0.50)		(3.00 NM RADIUS CCW (CFFWT))/4.98	2700	
OMPUE	WUNDU (RF) (FB) (RNP 0.50)		(2.40 NM RADIUS CCW (CFFWS))/1.82	2200	
MINRR (IAF)	YIPUT (TF) (FB) (RNP 0.70)		025.19 / 1.80	5000	
YIPUT (IF)	WAKUK (TF) (FB) (RNP 0.50)		026.07 / 2.53	4900	
WAKUK	IMHID (RF) (FB) (RNP 0.50)		(3.00 NM RADIUS CCW (CFFWT))/2.46	4200	
JOGUP (FAF)	RW20R (MAP) (TF) (FO) (RNP 0.30)		200.16 / 3.78		
RW20R (MAP)	BOSGE (TF) (FB) (RNP 1.00)		200.11 / 6.68		
BOSGE	AKIKE (RF) (FB) (RNP 1.00)		(5.00 NM RADIUS CCW (CFFWV)) / 14.87		
AKIKE	KRNKL (TF) (FO) (RNP 1.00)		029.77 / 3.69	4000	
NOTES, (CONT.):					
CHART NOTE: FOR INOPERATIVE ALS, INCREASE RNP 0.10 ALL CATS VISIBILITY TO RVR 5000.					
CHART SPEED ICON IN PLANVIEW AT ROAAD: MAX 210 KIAS.					
CHART SPEED ICON IN PLANVIEW AT MINRR: MAX 210 KIAS.					
CHART PLANVIEW NOTE AT WAKUK: MAX 180 KIAS UNTIL WUNDU.					
CHART PLANVIEW NOTE AT IMHID: MAX 180 KIAS UNTIL WUNDU.					
CHART PLANVIEW NOTE AT MUSHR: (RNP 0.30)					
CHART PLANVIEW NOTE AT MINRR: (RNP 0.30)					
CHART PLANVIEW NOTE AT ROAAD: (RNP 0.30)					
CITY AND STATE		ELEVATION: 439	TDZE: 439	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
FAIRBANKS, AK		AIRPORT NAME:		RNAV	RNAV (RNP) Z RWY 20R, AMDT 1
		FAIRBANKS INTL			22 JUNE 2017
					SUP:
					AMDT: ORIG-A
					DATED: 11/13/2014



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV (RNP) - STANDARD,  
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY  
20  
CHECKED

CITY AND STATE

FAIRBANKS, AK

ELEVATION: 439

TDZE: 439

AIRPORT NAME:

FAIRBANKS INTL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (RNP) Z RWY 20R, AMDT 1

22 JUNE 2017

SUP:

AMDT: ORIG-A

DATED: 11/13/2014