

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
VIOLA	ENIBY (FB)	129.02 / 24.29	2500	LPV: DA LNAV/VNAV: DA LNAV: RW33
ENIBY (IAF)	PETSE (FB)	062.19 / 5.00	2500	
RSW VORTAC (IAF)	PETSE (FB)	339.08 / 14.70	2500	CLIMB TO 2000 DIRECT APZUL AND HOLD.
PETSE (IF)	DODIK (FB)	332.23 / 6.10	1600	
DODIK (FAF)	RW33 (MAP) (FO)	332.20 / 4.75		ADDITIONAL FLIGHT DATA: HOLD NW, RT, 152.13 INBOUND. CHART FAS OBST: 104 TREE 265413N/0815917W CHART FAS OBST: 220 ANTENNA 265139N/0815830W DISTANCE TO THLD FROM 292 HATH: 0.78 NM. WAAS CHANNEL # 93507 REFERENCE PATH ID: W33A LTP HAE: -17 M
RW33 (MAP)	315 MSL	332.20		
315 MSL	APZUL (FO)		2000	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- PROFILE STARTS AT PETSE
- FAC: 332.20 FAF: DODIK DIST FAF TO MAP: 4.75 THLD: 4.75
- MIN. ALT: PETSE 2500, DODIK 1600
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 1600 GS ALT AT: DODIK 1600 OM: MM: IM:
- GS ANGLE: 3.00 TCH: 45.0 34:1 IS NOT CLEAR
- MSA FROM: RW33 2600

MAG VAR: 3W EPOCH YEAR: 1990

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	315	1	292	315	1	292	315	1	292	315	1	292			
LNAV/VNAV DA	374	1 1/4	351	374	1 1/4	351	374	1 1/4	351	374	1 1/4	351			
LNAV MDA	520	1	497	520	1	497	520	1 1/4	497	520	1 1/2	497			
CIRCLING	520	1	494	580	1	554	580	1 1/2	554	580	2	554			

NOTES:
CHART NOTE: BARO-VNAV NA WHEN USING PAGE FIELD ALTIMETER SETTING.
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F).
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
(SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE PUNTA GORDA, FL	ELEVATION: 26 THRE: 23 AIRPORT NAME: PUNTA GORDA	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 33, ORIG-A 31 MAY 2012	SUP:
				AMDT: ORIG
				DATED 06/05/2008

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON RSW VORTAC AIRWAY RADIALS 312 CW 016.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PAGE FIELD ALTIMETER SETTING AND INCREASE ALL DA 50 FEET AND ALL MDA 60 FEET; INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE, INCREASE LNAV CATS C AND D VISIBILITY 1/4 MILE, AND INCREASE CIRCLING CAT C VISIBILITY 1/4 MILE.

QUALITY
2
CHECKED

CITY AND STATE

PUNTA GORDA, FL

ELEVATION: 26

THRE: 23

AIRPORT NAME:

PUNTA GORDA

**FACILITY
IDENTIFIER:**
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 33, ORIG-A

31 MAY 2012

SUP:

AMDT: ORIG

DATED: 06/05/2008

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KPGD
RUNWAY	RW33
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W33A
LTP/FTP LATITUDE	265436.8120N
LTP/FTP LONGITUDE	0815924.8545W
LTP/FTP ELLIPSOIDAL HEIGHT	-00170
FPAP LATITUDE	265553.5400N
FPAP LONGITUDE	0820015.9300W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1016
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

9E9BCEF7

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00070
FPAP ORTHOMETRIC HEIGHT	+00070

CITY AND STATE

PUNTA GORDA, FL

ELEVATION: 26

THRE: 23

AIRPORT NAME:

PUNTA GORDA

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 33, ORIG-A

31 MAY 2012

SUP:

AMDT: ORIG

DATED: 06/05/2008

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
1
CHECKED

CITY AND STATE PUNTA GORDA, FL	ELEVATION: 26	THRE: 23	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 33. ORIG-A 31 MAY 2012	SUP:	
	AIRPORT NAME:				AMDT:	ORIG
	PUNTA GORDA				DATED:	06/05/2008

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
PP	12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KPGDK7PR33	RW33	001	0000W33A0N2654368120W08159248545-001700300N2655535400W08200159300106751016000450F4005009E9BCEF7									
	SUSAP KPGDK7PR33	RW33	002E	+00070+00070LPV	93507								

	1	2	3	4	5	6	7	8	9	0	1	2	3
MSA	12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KPGDK7SRW33 K7PG			0	18018002625							M	

CITY AND STATE
PUNTA GORDA, FL

ELEVATION: 26 THRE: 23
AIRPORT NAME:
PUNTA GORDA

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 33, ORIG-A
31 MAY 2012

SUP:
AMDT: ORIG
DATED: 06/05/2008

QUALITY
1
CHECKED