

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
NETKE (IAF)	CIMIX (NOPT) (FB)	156.55 / 5.00	3000	LPV: DA LNAV/VNAV: DA LNAV: RW07 CLIMB TO 3000 DIRECT HOPAX AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 246.87 INBOUND. CHART FAS OBST: 1015 TOWER 391242N/0821538W CHART FAS OBST: 1110 TOWER 391052N/0821657W DISTANCE TO THLD FROM 440 HAT: 1.26 NM. CHART VDP AT 1.80 MILES TO RW07* *LNAV ONLY. WAAS CHANNEL # 81916 REFERENCE PATH ID: W07A
SOYLO (IAF)	CIMIX (NOPT) (FB)	336.61 / 5.00	3000	
CIMIX (IF/IAF)	FEKLO (FB)	066.58 / 6.19	2600	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD SW CIMIX, RT, 066.58 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 066.65 FAF: FEKLO DIST FAF TO MAP: 5.56 THLD: 5.56
- MIN. ALT: CIMIX 3000, FEKLO 2600
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 2600 GS ALT AT: FEKLO OM: MM: IM:
- GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 6W

EPOCH YEAR: 1995

MINIMUMS

TAKEOFF: <u> </u>	<input type="checkbox"/> STANDARD	<input checked="" type="checkbox"/> X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	<input type="checkbox"/> X										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1205	1 1/2	440	1205	1 1/2	440	1205	1 1/2	440	1205	1 1/2	440			
LNAV/VNAV DA	1334	2	569	1334	2	569	1334	2	569	1334	2	569			
LNAV MDA	1360	1	595	1360	1	595	1360	1 1/2	595	1360	1 3/4	595			
CIRCLING	1380	1	614	1420	1	654	1420	1 3/4	654	1420	2	654			

NOTES:
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 47C (116F).
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PROFILE NOTE: VGS/ AND RNAV GLIDEPATH NOT COINCIDENT.
 SEE 8260-10

QUALITY
1
CHECKED

CITY AND STATE ATHENS/ALBANY, OH	ELEVATION: 766 TDZE: 765 AIRPORT NAME: OHIO UNIVERSITY SNYDER FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, AMDT 1 11 FEB 2010	SUP:
				AMDT: ORIG-A
				DATED 12/22/2005

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PARKERSBURG, WV ALTIMETER SETTING AND INCREASE ALL DA/MDA 100 FEET, INCREASE LPV AND LNAV/VNAV ALL CATS, LNAV AND CIRCLING CATS C AND D VISIBILITY 1/2 MILE AND CIRCLING CAT B VISIBILITY 1/4 MILE.

CHART NOTE: BARO-VNAV AND VDP NA WHEN USING PARKERSBURG, WV ALTIMETER SETTING.

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	337/30 CW 157/30 (NOPT)	CIMIX (IF/AF) (FB)	3000
2.	157/30 CW 247/30	NETKE (IAF) (FB)	3000
3.	247/30 CW 337/30	SOYLO (IAF) (FB)	3000

QUALITY
1
CHECKED

CITY AND STATE

ATHENS/ALBANY, OH

ELEVATION: 766

TDZE: 765

AIRPORT NAME:

OHIO UNIVERSITY SNYDER FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 7, AMDT 1

11 FEB 2010

SUP:

AMDT: ORIG-A

DATED: 12/22/2005

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KUNI
RUNWAY	RW07
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W07A
LTP/FTP LATITUDE	391233.6330N
LTP/FTP LONGITUDE	0821406.3755W
LTP/FTP ELLIPSOIDAL HEIGHT	+01984
FPAP LATITUDE	391317.2300N
FPAP LONGITUDE	0821226.3800W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1320
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

44BCB133

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02325
FPAP ORTHOMETRIC HEIGHT	+02325

QUALITY
1
CHECKED

CITY AND STATE
ATHENS/ALBANY, OH

ELEVATION: 766 TDZE: 765
AIRPORT NAME:
OHIO UNIVERSITY SNYDER FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 7, AMDT 1
11 FEB 2010

SUP:
AMDT: ORIG-A
DATED: 12/22/2005

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

NAR	CIMIX
NAR	FEKLO
NAR	HOPAX
NAR	NETKE
NAR	SOYLO

[illegible]

SUSAP KUNIK5AUNI 0 056YHN39124281W082134532W006000766 1800018000C MNAR OHIO UNIVERSITY SNYDER FIELD

[illegible]

SUSAP KUNIK5FR07	ACIMIX	010CIMIXK5EA0EE	AR	HF	06660040	+	03000	18000	A	JS
SUSAP KUNIK5FR07	ANETKE	010NETKEK5EA0E	A	IF				18000	A	JS
SUSAP KUNIK5FR07	ANETKE	020CIMIXK5EA0EE	B	010TF	15660050	+	03000		A	JS
SUSAP KUNIK5FR07	ASOYLO	010SOYLOK5EA0E	A	IF				18000	A	JS
SUSAP KUNIK5FR07	ASOYLO	020CIMIXK5EA0EE	B	010TF	33660050	+	03000		A	JS
SUSAP KUNIK5FR07	R	010CIMIXK5EA0E	I	IF		+	03000	18000	A	JS
SUSAP KUNIK5FR07	R	020FEKLOK5EA1E	F	051TF	06660062	+	02600		A	JS
SUSAP KUNIK5FR07	R	020FEKLOK5EA2WALPV		ALNAV/VNAV ALNAV						JS
SUSAP KUNIK5FR07	R	030RW07 K5PGOGY	M	031TF	06670056		00803	-300	A	JS
SUSAP KUNIK5FR07	R	040	0	M 010CA	0667	+	01166		A	JS
SUSAP KUNIK5FR07	R	050HOPAXK5EA0EY		010DF		+	03000		A	JS
SUSAP KUNIK5FR07	R	060HOPAXK5EA0EE		R020HM	24690040	+	03000		A	JS

[illegible]

SUSAP KUNIK5GRW07 0056000667 N39123363W082140638-0100 +0198400763090040100R

[illegible]

SUSAP KUNIK5PR07 RW07 001 0000W07A0N3912336330W08214063755+019840300N3913172300W08212263800106751320000400F40050044BCB133

QUALITY
1
CHECKED

SUP:	
AMDT:	ORIG-A
DATED:	12/22/2005

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
1
CHECK

SUP:	
AMDT:	ORIG-A
DATED:	12/22/2005