

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES								MISSED APPROACH				
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW04 CLIMB TO 600 THEN CLIMBING LEFT TURN TO 2000 DIRECT MAGGO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 037.01 INBOUND: FAS OBST: 254 AAO 375300N/0753110W CHART R-4006. CHART R-6604. DISTANCE TO THLD FROM 250 HATH: 0.61 NM. CHART VDP AT 1.47 MILES TO RW04* *LNAV ONLY. WAAS CHANNEL # 56331 REFERENCE PATH ID: W04A CHART CIRCLING ICON. LTP HAE: -26.2 M				
CURAB (IF/IAF)		RIMUE (FB)		043.11 / 6.00		1700						
RIMUE (FAF)		RW04 (MAP) (FO)		043.15 / 5.05								
RW04 (MAP)		600 MSL		043.15		600						
600 MSL		MAGGO (FO)				2000						
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD SW CURAB, RT, 043.11 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: 043.15 FAF: RIMUE DIST FAF TO MAP: 5.05 THLD: 5.05 4. MIN. ALT: CURAB 2000, RIMUE 1700 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: 1700 GS ALT AT: RIMUE 1700 OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: 3.00 TCH: 56.6 34:1 IS CLEAR 8. MSA FROM: <u> </u>								MAG VAR: 11W EPOCH YEAR: 2015				
MINIMUMS												
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		STANDARD @				
CATEGORY =====>		A		B		C		D		E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	284	3/4	250	284	3/4	250	284	3/4	250	284	3/4	250
LNAV/VNAV DA	452	1 3/8	418	452	1 3/8	418	452	1 3/8	418	452	1 3/8	418
LNAV MDA	560	1	526	560	1	526	560	1 1/2	526	560	1 1/2	526
CIRCLING	600	1	560	600	1	560	620	1 1/2	580	860	2 3/4	820
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -11C (13F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN RWY 10 VGS I INOPERATIVE, CIRCLING TO RWY 10 NA AT NIGHT. (SEE FORM 8260-10)												
CITY AND STATE		ELEVATION: 40 THRE: 34		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:		
WALLOPS ISLAND, VA		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 4, AMDT 1				AMDT: ORIG		
		WALLOPS FLIGHT FACILITY				19 SEPTEMBER 2013				DATED: 07/10/2003		

QUALITY
 2
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SALISBURY ALTIMETER SETTING: INCREASE LPV DA TO 342 AND ALL CATS VISIBILITY 1/4 MILE; INCREASE LNAV/VNAV DA TO 510 AND ALL CATS VISIBILITY 1/4 MILE; INCREASE ALL MDA 60 FEET AND LNAV CATS C/D AND CIRCLING CAT C VISIBILITY 1/4 MILE.

CHART NOTE: BARO-VNAV AND VDP NA WHEN USING SALISBURY ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	313/30 CW 133/30 (NOPT)	CURAB (IF/IAF) (FB)	2000
2.	133/30 CW 313/30	CURAB (IF/IAF) (FO)	2000

QUALITY
2
CHECKED

CITY AND STATE
WALLOPS ISLAND, VA

ELEVATION: 40 THRE: 34
AIRPORT NAME:
WALLOPS FLIGHT FACILITY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 4, AMDT 1
19 SEPTEMBER 2013

SUP:
AMDT: ORIG
DATED: 07/10/2003

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KWAL
RUNWAY RW04
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W04A
LTP/FTP LATITUDE 375537.4510N
LTP/FTP LONGITUDE 0752815.4100W
LTP/FTP ELLIPSOIDAL HEIGHT -00262
FPAP LATITUDE 375652.9360N
FPAP LONGITUDE 0752715.4020W
THRESHOLD CROSSING HEIGHT (TCH) 00056.6
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 0080
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

2E306A43

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K6
LTP ORTHOMETRIC HEIGHT +00104
FPAP ORTHOMETRIC HEIGHT +00104

CITY AND STATE

WALLOPS ISLAND, VA

ELEVATION: 40

THRE: 34

AIRPORT NAME:

WALLOPS FLIGHT FACILITY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 4, AMDT 1

19 SEPTEMBER 2013

SUP:

AMDT:

ORIG

DATED:

07/10/2003

QUALITY
2
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
2
CHECKED

CITY AND STATE WALLOPS ISLAND, VA	ELEVATION: 40 THRE: 34	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 19 SEPTEMBER 2013	SUP:
	AIRPORT NAME: WALLOPS FLIGHT FACILITY			AMDT: ORIG
				DATED: 07/10/2003

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated; except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	CURAB	CURAB	010	IAF	HF	R	FO		043.1 (032.1T)	005.0	AA 02000	
		CURAB	010	FACF	IF		FB				AA 02000	
		RIMUE	020	FAF	TF		FB	0.5	043.1 (032.1T)	006.0	AA 01700	
		RW04	030	MAP	TF		FO	0.3	043.2 (032.2T)	005.1	AT 00091	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		043.2 (032.2T)		AA 00600	
	MAGGO	050		DF	L	FO				AA 02000	
	MAGGO	060		HM	R	FO		037.0 (026.0T)	005.0	AA 02000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CURAB	N374615.29	W0753541.03	N3746.255	W07535.684
	MAGGO	N375858.48	W0754401.39	N3758.975	W07544.023
	RIMUE	N375120.49	W0753139.38	N3751.342	W07531.656
	RW04	N375537.45	W0752815.41	N3755.624	W07528.257

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW04	00034	57

QUALITY
2
CHECKED

CITY AND STATE WALLOPS ISLAND, VA	ELEVATION: 40	THRE: 34	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 19 SEPTEMBER 2013	SUP:
	AIRPORT NAME: WALLOPS FLIGHT FACILITY				AMDT: ORIG
					DATED: 07/10/2003