

PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/22/13	KY	Paducah	Barkley Rgnl	3/6222	7/2/13	RNAV (GPS) RWY 22, Orig-B

FDC **3/6222** PAH FI/P IAP BARKLEY RGNL, PADUCAH, KY. RNAV (GPS) RWY 22, ORIG-B... LNAV MDA ALL CATS 820/HAT 418, CAT C VISIBILITY 1 1/4. CHANGE UNCOMPENSATED BARO-VNAV SYSTEMS NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). CHANGE HELICOPTER VISIBILITY REDUCTION NOTE TO READ: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHANGE LOCAL ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MAYFIELD ALTIMETER SETTING AND INCREASE LPV DA TO 738, LNAV/VNAV DA TO 850 AND ALL MDA 80 FEET, AND INCREASE LPV ALL CATS VISIBILITY TO 1 1/4, LNAV/VNAV ALL CATS VISIBILITY TO 1 3/4, LNAV CAT D VISIBILITY TO 1 1/2. CHART NOTE: CIRCLING TO RWY 14 NA AT NIGHT. CHART FAS OBSTACLE 559 MSL TOWER 370546.84N/0884235.27W. THIS IS RNAV (GPS) RWY 22, ORIG-C.