

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW22 CLIMB TO 3000 DIRECT KUYRE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 041.96 INBOUND. CHART FAS OBST: 229 TOWER 323200N/0920132W CHART: ASR. DISTANCE TO THLD FROM 200 HATH: 0.46 NM. WAAS CHANNEL # 70510 REFERENCE PATH ID: W22A LTP HAE: -3.2 M						
LURBY (IF/IAF)		IBECI (FB)		222.13 / 7.00			1700								
IBECI (FAF)		UTPEF/1.40 NM TO RW22 (FB)		222.08 / 3.53											
UTPEF/1.40 NM TO RW22		RW22 (MAP) (FO)		222.05 / 1.40											
RW22 (MAP)		275 MSL		222.05											
275 MSL		KUYRE (FO)					3000								
1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF) 2. HOLD NE LURBY, RT, 222.13 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAF: 222.08 FAF: IBECI DIST FAF TO MAP: 4.93 THLD: 4.93 4. MIN. ALT: LURBY 2000, IBECI 1700, UTPEF/1.40 NM TO RW22 560* 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: 1700 GS ALT AT: IBECI 1700 OM: MM: IM: 7. GS ANGLE: 3.00 TCH: 54.1 34:1 IS CLEAR 8. MSA FROM:										MAG VAR: 3E		EPOCH YEAR: 1995			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	275	1/2	200	275	1/2	200	275	1/2	200	275	1/2	200			
LNAV/VNAV DA	390	1/2	315	390	1/2	315	390	1/2	315	390	1/2	315			
LNAV MDA	480	1/2	405	480	1/2	405	480	3/4	405	480	3/4	405			
CIRCLING	580	1	501	580	1	501	620	1 1/2	541	640	2	561			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP 0.3 NA. *LNAV ONLY															
CITY AND STATE MONROE, LA		ELEVATION: 79 THRE: 75 AIRPORT NAME: MONROE RGNL		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, AMDT 1 15 NOVEMBER 2012				SUP: AMDT: ORIG-A DATED 06/03/2010					

717.73 Rals 11/15/CL