

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES								MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LNAV: RW35 CLIMB TO 4300 DIRECT INDOV AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 168.35 INBOUND. FAS OBST: 2749 AAO 371300N/1002029W MOCSY TO RWY 35: 3.00/40							
FLACK		LATOC (FO)		166.87 / 10.15		4300									
LATOC (IF/IAF)		MOCSY (FB)		348.37 / 6.80		4100									
MOCSY (FAF)		RW35 (MAP) (FO)		348.36 / 4.89											
RW35 (MAP)		2929 MSL		348.36											
2929 MSL		INDOV (FO)				4300									
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD S LATOC, RT, 348.37 INBOUND, 4300 FT. IN LIEU OF PT (IAF) 3. FAC: 348.36 FAF: MOCSY DIST FAF TO MAP: 4.89 THLD: 4.89 4. MIN. ALT: LATOC 4300, MOCSY 4100 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW35 4800								MAG VAR: 8E EPOCH YEAR: 2000							
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A X							
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	3000	1	498	3000	1	498		NA			NA				
CIRCLING	3000	1	471	3000	1	471		NA			NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT LATOC ON V516 WESTBOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FLACK ON V17 NORTHWEST BOUND AND V234 NORTHEAST (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 2529 THRE: 2502		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
MEADE, KS		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 35, ORIG				AMDT: NONE					
		MEADE MUNI				13 JAN 2011				DATED					

QUALITY
4
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):
BOUND.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LIBERAL ALTIMETER SETTING AND INCREASE ALL MDA 140 FEET.

CHART NOTE: VGS1 AND DESCENT ANGLES NOT COINCIDENT.

QUALITY
4
CHECKED

CITY AND STATE MEADE, KS	ELEVATION: 2529 THRE: 2502 AIRPORT NAME: MEADE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG 13 JAN 2011	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

4

CITY AND STATE MEADE, KS	ELEVATION: 2529 THRE: 2502	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG 13 JAN 2011	SUP:
	AIRPORT NAME: MEADE MUNI			AMDT: NONE
				DATED: