

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**VOR STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - FAR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 6.18 MILES AFTER CCT VORTAC
MAHEN/CCT 9.78 DME (IF/IAF)	CCT VORTAC (NOPT)	259.36 / 9.78	2100	CLIMB TO 2000 THEN CLIMBING LEFT TURN 2500 DIRECT CCT VORTAC AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD E, LT, 259.10 INBOUND. CHART FAS OBST: 559 TREE 372239N/0871600W CHART TDZE 418

- PT R SIDE OF COURSE 079.10 OUTBOUND 2500 FT WITHIN 10 MILES OF CCT VORTAC (IAF)
- 
- FAC 259.10 FAF CCT VORTAC DIST FAF TO MAP 6.18 THLD 6.18
- MIN. ALT CCT VORTAC 2100
- MSA FROM: CCT VORTAC 2600

MAG VAR: 1W EPOCH YEAR: 1990

**MINIMUMS**

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		X						
CATEGORY =====>		A			B			C			D			E				
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-23		820	1	402	820	1	402	820	1 1/4	402	820	1 1/4	402					
CIRCLING		880	1	441	900	1	461	900	1 1/2	461	1000	2	561					

**NOTES:**

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.  
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EVANSVILLE REGIONAL ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET, AND INCREASE S-23 CATS C AND D VISIBILITY 1/4 MILE.

CITY AND STATE MADISONVILLE, KY	ELEVATION: 439 TDZE: 418 AIRPORT NAME: MADISONVILLE MUNI	FACILITY IDENTIFIER: CCT	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 23, AMDT 14 07 MAY 2009	SUP VOR OR GPS RWY 23 AMDT 13 DATE 09/28/2006
------------------------------------	--	-----------------------------	--	--

Pub 05107109

TL 09-09

QUALITY  
CONTROLLED