U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
ROACH INT	SHY VOR/DME	143.36 / 12.40	3100
SGF VORTAC	SHY VOR/DME	036.11 / 53.83	3100
TBN VOR	SHY VOR/DME	306.22 / 28.35	2800
VIH VOR/DME	SHY VOR/DME	255.17 / 42.96	2800

MISSED APPROACH

MAP: 5.70 MILES AFTER SHY VOR/DME OR AT MAGYU/5.70 DME FIX

CLIMB TO 3100 THEN LEFT TURN DIRECT SHY VOR/DME AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD NE, LT, 226.53 INBOUND.
FAS OBST: 1219 AAO 380000N/0923747W
FAC CROSSES MID POINT RWY 15-33

1. PT R SIDE OF COURSE 046.53 OUTBOUND 2800 FT WITHIN 10 MILES OF SHY VOR/DME (IAF)
2.
3. FAC 226.53 FAF SHY VOR/DME DIST FAF TO MAP 5.70 THLD
4. MIN. ALT SHY VOR/DME 2800
8. MSA FROM: SHY VOR/DME 270-140 2600, 140-270 3100

MAG VAR: 0E EPOCH YEAR:2015

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A STANDARD @

CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	1540	1	478	1540	1	478		NA			NA				

NOTES:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LEE C FINE MEMORIAL ALTIMETER SETTING AND INCREASE ALL MDA 60 FT.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY 24 CHECKED

CITY AND STATE	ELEVATION: 1062 TDZE: AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP
CAMDENTON, MO	CAMDENTON MEMORIAL-LAKE RGNL	SHY	VOR-A, AMDT 5B 25 JUNE 2015	AMDT 5A
				DATE 05/02/2013

FAA FORM 8260-5 / April 2006 (computer generated)