

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW32  CLIMB TO 1500 THEN CLIMBING LEFT TURN TO 3000 DIRECT LUFEV AND HOLD.  ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1033 TREE 331335N/0841604W 1109 AAO 331059N/0841216W DISTANCE TO THLD FROM 250 HATH: 0.66 NM. CHART VDP AT 1.06 MILES TO RW32* *LNAV ONLY. WAAS CHANNEL # 65729 REFERENCE PATH ID: W32A LTP HAE: 257.1 M											
ETZIM (IAF)	LUFEV (NOPT) (FB)	050.97 / 5.00	3000												
IDEVY (IAF)	LUFEV (NOPT) (FB)	231.05 / 5.00	3000												
LUFEV (IF/IAF)	ZUKSI (FB)	321.01 / 6.16	2200												
ZUKSI (FAF)	RW32 (MAP) (FO)	320.96 / 3.84	1500												
RW32 (MAP)	1500 MSL	320.96	3000												
1500 MSL	LUFEV (FO)														
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. HOLD SE LUFEV, LT, 321.01 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 320.96 FAF: ZUKSI DIST FAF TO MAP: 3.84 THLD: 3.84 4. MIN. ALT: LUFEV 3000, ZUKSI 2200 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: 2200 GS ALT AT: ZUKSI 2200 OM: MM: IM: 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR 8. MSA FROM:				MAG VAR: 4W EPOCH YEAR: 2000											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT															
ALTERNATE: N A X															
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1187	7/8	250	1187	7/8	250		NA			NA				
LNAV/VNAV DA	1187	7/8	250	1187	7/8	250		NA			NA				
LNAV MDA	1300	1	363	1300	1	363		NA			NA				
CIRCLING	1400	1	442	1560	1	602		NA			NA				
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 958 THRE: 937		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
GRIFFIN, GA		AIRPORT NAME: GRIFFIN-SPALDING COUNTY				RNAV (GPS) RWY 32, ORIG 26 JULY 2012				AMDT: NONE					
										DATED					

TC 12-16 Pub 07/26/12