

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 4.14 MILES AFTER FOR NDB
MLS VOR/DME	FOR NDB	238.79 / 24.34	6000	CLIMB TO 3500 THEN CLIMBING RIGHT TURN TO 4900 DIRECT FOR NDB AND HOLD.
MLS VOR/DME (IAF)	ASHLI/MLS 14.00 DME (NOPT)	238.81 / 14.00	5000	
ASHLI/MLS 14.00 DME (IF)	FOR NDB	242.37 / 10.34	4000	
				ADDITIONAL FLIGHT DATA: HOLD W, RT, 081.36 INBOUND. FAS OBST: 2939 AAO 461451N/1063228W 2959 AAO 461518.88N/1063059.33W FOR NDB TO RW26: 2.81/40.

1. PT L SIDE OF COURSE 062.37 OUTBOUND 4900 FT WITHIN 10 MILES OF FOR NDB (IAF)
2.
3. FAC 261.36 FAF FOR NDB DIST FAF TO MAP 4.14 THLD 4.14
4. MIN. ALT FOR NDB 4000
8. MSA FROM: FOR NDB 090-270 5500, 270-090 4600

MAG VAR: 11E EPOCH YEAR: 2010

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A	X							
CATEGORY >>>>>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-26	3340	1	612	3340	1	612	3340	1 3/4	612	3340	1 3/4	612			
CIRCLING	3340	1	611	3340	1	611	3400	2	671	3400	2 1/4	671			

NOTES:

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
CHART NOTE: USE MILES CITY ALTIMETER SETTING, WHEN NOT RECEIVED, EXCEPT FOR OPERATORS WITH APPROVED WEATHER REPORTING SERVICES, PROCEDURE NA.
(SEE FORM 8260-10)

QUALITY
1
CHECKED

CITY AND STATE FORSYTH, MT	ELEVATION: 2729 AIRPORT NAME: TILLITT FIELD	THRE: 2728 FACILITY IDENTIFIER: FOR	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 26, AMDT 3 09 FEB 2012	SUP
				AMDT 2A
				DATE 03/15/2007

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):**CHART NOTE: WHEN VGSI INOP, PROCEDURE NA AT NIGHT.****CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON MLS VORTAC AIRWAY RADIALS 239 CW 271.**

CITY AND STATE

FORSYTH, MT

ELEVATION: 2729

THRE: 2728

AIRPORT NAME:

TILLITT FIELD

FACILITY
IDENTIFIER:

FOR

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

NDB RWY 26, AMDT 3

09 FEB 2012

SUP:

AMDT

2A

DATED:

03/15/2007