

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION LOC STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: 3.98 NM AFTER TUCFY INT/I-OBG 5.00 DME OR AT I-OBG 1.03 DME						
FLAGG INT		ITR NDB			153.92 / 18.73			7000		CLIMB TO 7000 DIRECT ITR NDB AND HOLD, CONTINUE CLIMB-IN-HOLD TO 7000.						
ITR NDB		KURIQ INT/I-OBG 2.06 DME			158.90 / 1.65			7000		ALTERNATE MA (DO NOT CHART): CLIMB TO 5000 THEN CLIMBING RIGHT TURN TO 7000 DIRECT GLD VORTAC AND HOLD.						
										ADDITIONAL FLIGHT DATA: HOLD NW, RT, 139.00 INBOUND. FAS OBST: 4420 AAO 391105N/1021451W. CHART GLD 28.94 DME AT KURIQ INT CHART COUGAR MOA. CHART CIRCLING ICON. TUCFY TO RW33: 3.00/32 CHART VDP AT 2.42 DME; DISTANCE VDP TO THLD 1.40 NM. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD SE GLD VORTAC, RT, 332.37 INBOUND CHART (CFDTB) AT (390446.28N/1021231.72W). CHART PLANVIEW NOTE: ADF OR DME REQUIRED.						
1. PT <u>L</u> SIDE OF COURSE <u>153.90</u> OUTBOUND <u>6300</u> FT WITHIN <u>10</u> MILES OF <u>KURIQ</u> (IAF)																
2.																
3. FAC <u>333.90</u> FAF <u>TUCFY INT/I-OBG 5.00 DME</u> DIST FAF TO MAP <u>3.98</u> THLD <u>3.98</u>																
4. MIN. ALT <u>TUCFY INT/I-OBG 5.00 DME 5500</u>																
8. MSA FROM: <u>ITR NDB 6300</u>										MAG VAR: 6E EPOCH YEAR: 2020						
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X							
CATEGORY =====>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-33	4680	1	475	4680	1	475	4680	1 3/8	475	4680	1 3/8	475				
CIRCLING	4680	1	462	4680	1	462	4860	1 3/4	642	4860	2	642				
NOTES:																
CHART NOTE: ADF REQUIRED.																
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FLAGG ON V4 WESTBOUND.																
CITY AND STATE		ELEVATION: 4218 TDZE: 4205			FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP		QUALITY 8 CHECKED			
BURLINGTON, CO		AIRPORT NAME:			I-OBG		LOC RWY 33, AMDT 1 1 FEBRUARY 2018				AMDT		ORIG-A			
		KIT CARSON COUNTY									DATE		11/13/2014			

LOC STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
8
CHECKED

CITY AND STATE

BURLINGTON, CO

ELEVATION: 4218

TDZE: 4205

AIRPORT NAME:

KIT CARSON COUNTY

FACILITY
IDENTIFIER:

I-OBG

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

LOC RWY 33, AMDT 1

1 FEBRUARY 2018

SUP:

AMDT: ORIG-A

DATED: 11/13/2014