

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE				ALTITUDE		MAP: OMN 16.51 DME FIX							
OMN VORTAC (IAF)			DONGS/ 11.83 DME			211.77 / 11.83				1600		CLIMBING RIGHT TURN TO 2000 DIRECT OMN VORTAC AND HOLD.							
										ADDITIONAL FLIGHT DATA: HOLD NW, LT, 156.00 INBOUND. CHART FAS OBST: 309 TOWER 290620N/0811252W CHART: ASR DONGS TO RW23: 3.00/40.									
1. PT <u>NA</u> SIDE OF COURSE <u>OUTBOUND</u> <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)																			
2. PROFILE STARTS AT OMN VORTAC																			
3. FAC <u>211.77</u> FAF <u>DONGS/ 11.83 DME</u> DIST FAF TO MAP <u> </u> THLD <u>4.68</u>																			
4. MIN. ALT <u>OMN VORTAC 1600, DONGS 1600</u>																			
8. MSA FROM: <u>OMN VORTAC 2800</u>										MAG VAR: 0E EPOCH YEAR:1965									
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X									
CATEGORY =====>		A			B			C			D			E					
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA				
S-23	540	1	472	540	1	472	540	1 3/8	472	540	1 3/8	472							
CIRCLING	600	1	520	600	1	520	600	1 1/2	520	640	2	560							
NOTES:																			
CHART NOTE: STRAIGHT-IN/CIRCLING RWY 23 AND CIRCLING TO RWY 12 NA AT NIGHT.																			
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DAYTONA BEACH INTL ALTIMETER SETTING AND INCREASE ALL MDAS 40 FEET.																			
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. (SEE FORM 8260-10)																			
CITY AND STATE DELAND, FL				ELEVATION: 80 THRE: 68 AIRPORT NAME: DELAND MUNI-SIDNEY H TAYLOR FIELD				FACILITY IDENTIFIER: OMN		PROCEDURE NO./AMD'T NO./EFFECTIVE DATE: VOR/DME RWY 23, ORIG 25 AUG 2011						SUP AMD'T NONE DATE			

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON OMN VORTAC AIRWAY RADIALS 161 CW 211.



CITY AND STATE

DELAND, FL

ELEVATION: 80

THRE: 68

AIRPORT NAME:

DELAND MUNI-SIDNEY H TAYLOR FIELD

FACILITY
IDENTIFIER:
OMN

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR/DME RWY 23, ORIG

25 AUG 2011

SUP:

AMDT: NONE

DATED: