

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
GGW VOR/DME	ATCHY (FO)	303.66 / 11.28	5000
KEEVR (IAF)	ATCHY (NOPT) (FB)	066.34 / 16.98	5000
ATCHY (IF/IAF)	CETAD (FB)	122.76 / 6.06	4000
CETAD (FAF)	GOSSI/1.70 NM TO RW12 (FB)	122.84 / 3.54	
GOSSI/1.70 NM TO RW12	RW12 (MAP) (FO)	122.89 / 1.70	
RW12 (MAP)	2541 MSL	122.89	
(SEE FORM 8260-10)			

MISSED APPROACH

LPV: DA  
LNAV/VNAV: DA  
LNAV: RW12

CLIMB TO 6000 DIRECT EZCUP AND ON TRACK 076.64 TO NEGAE AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD W, RT, 089.00 INBOUND.  
CHART FAS OBST: 2345 TOWER 481334N/1063653W  
DISTANCE TO THLD FROM 250 HATH: 0.66 NM.  
CHART VDP AT 0.85 MILES TO RW12\*  
\*LNAV ONLY.  
WAAS CHANNEL # 93620  
REFERENCE PATH ID: W12A  
LTP HAE: 681.3 M

1. PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
2. HOLD NW ATCHY, RT, 122.76 INBOUND, 5000 FT. IN LIEU OF PT (IAF)
3. FAC: 122.84 FAF: CETAD DIST FAF TO MAP: 5.24 THLD: 5.24
4. MIN. ALT: ATCHY 5000, CETAD 4000, GOSSI/1.70 NM TO RW12 2860\*
5. DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
6. MIN GS INCP: 4000 GS ALT AT: CETAD 4000 OM:        MM:        IM:
7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR
8. MSA FROM: RW12 4400

MAG VAR: 11E

EPOCH YEAR: 2010

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	2541	7/8	250	2541	7/8	250	2541	7/8	250	2541	7/8	250			
LNAV/VNAV DA	2584	1	293	2584	1	293	2584	1	293	2584	1	293			
LNAV MDA	2600	1	309	2600	1	309	2600	7/8	309	2600	7/8	309			
CIRCLING	2780	1	484	2780	1	484	2780	1 1/2	484	2860	2	564			

NOTES:  
CHART NOTE: DME/DME RNP-0.3 NA.  
CHART NOTE: VDP AND BARO-VNAV NA WHEN USING WOLF POINT ALTIMETER SETTING  
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV-VNAV NA BELOW -30C (-22F) OR ABOVE 29C (84F)  
(SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY  
2  
CHECKED

CITY AND STATE GLASGOW, MT	ELEVATION: 2296 THRE: 2291 AIRPORT NAME: WOKAL FIELD/GLASGOW INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMD T NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG <b>09 FEB 2012</b>	SUP: AMD T: NONE DATED
-------------------------------	-------------------------------------------------------------------------	---------------------------------	------------------------------------------------------------------------------------------	------------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
2541 MSL	EZCUP (FB)		
EZCUP	NEGAE (FO)	076.64 / 15.21	6000

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WOLF POINT ALTIMETER SETTING AND INCREASE ALL DA 141 FEET AND ALL MDA 160 FEET AND INCREASE LPV VISIBILITY ALL CATS 1/2 MILE, LNAV/VNAV VISIBILITY ALL CATS 1/2 MILE, LNAV VISIBILITY CATS C AND D 1/2 MILE, AND CIRCLING VISIBILITY CATS C AND D 1/4 MILE.

QUALITY  
2  
CHECKED

CITY AND STATE  
GLASGOW, MT

ELEVATION: 2296      THRE: 2291  
AIRPORT NAME:  
WOKAL FIELD/GLASGOW INTL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 12, ORIG  
09 FEB 2012

SUP:  
AMDT: NONE  
DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0  
SBAS SERVICE PROVIDER IDENTIFIER 0  
AIRPORT IDENTIFIER KGGW  
RUNWAY RW12  
APPROACH PERFORMANCE DESIGNATOR 0  
ROUTE INDICATOR 0  
REFERENCE PATH DATA SELECTOR W12A  
REFERENCE PATH IDENTIFIER (APPROACH ID) 481300.6205N  
LTP/FTP LATITUDE 1063720.9825W  
LTP/FTP LONGITUDE +06813  
LTP/FTP ELLIPSOIDAL HEIGHT 481158.8600N  
FPAP LATITUDE 1063545.0300W  
FPAP LONGITUDE 00040.0  
THRESHOLD CROSSING HEIGHT (TCH) F  
TCH UNITS SELECTOR (METERS OR FEET USED) 03.00  
GLIDEPATH ANGLE (GPA) 106.75  
COURSE WIDTH AT THRESHOLD 1224  
LENGTH OFFSET 40.0  
HORIZONTAL ALERT LIMIT (HAL) 50.0  
VERTICAL ALERT LIMIT (VAL)

CRC REMAINDER

7126B838

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K1  
LTP ORTHOMETRIC HEIGHT +06982  
FPAP ORTHOMETRIC HEIGHT +06982

QUALITY  
2  
CHECKED

CITY AND STATE  
GLASGOW, MT

ELEVATION: 2296 THRE: 2291  
AIRPORT NAME:  
WOKAL FIELD/GLASGOW INTL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 12, ORIG

09 FEB 2012

SUP:  
AMDT: NONE  
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY  
CHECKED

CITY AND STATE GLASGOW, MT	ELEVATION: 2296      THRE: 2291	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
	AIRPORT NAME:		RNAV (GPS) RWY 12, ORIG	AMDT:      NONE
	WOKAL FIELD/GLASGOW INTL		09 FEB 2012	DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP KGGWK1GRW12 0050011229 N48130062W106372098-0100 +0681302291000040100R

SUSAP	KGGWK1PR12	RW12	001	0000W12A0N4813006205W10637209825+068130300N4811588600W10635450300106751224000400F4005007126B838
SUSAP	KGGWK1PR12	RW12	002E	+06982+06982LPV 93620

SUSAP KGGWK1SRW12 K1PG 0 18018004425 M

QUALITY  
CHECKED