

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: MKR NDB						
										CLIMB TO 4000 IN MKR NDB HOLDING PATTERN.						
										ADDITIONAL FLIGHT DATA: HOLD E, RT, 278.00 INBOUND. FAS OBST: 2539 AAO 481247N/1062841W FAC CROSSES RWY C/L EXTENDED 3026 FROM THLD.						
1. PT <u> L </u> SIDE OF COURSE <u> 098.00 </u> OUTBOUND <u> 4000 </u> FT WITHIN <u> 10 </u> MILES OF <u> MKR NDB </u> (IAF) 2. _____ 3. FAC <u> 278.00 </u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT _____ 8. MSA FROM: MKR NDB 4400										MAG VAR: 11E EPOCH YEAR: 2010						
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @						
CATEGORY ==>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-30	2900	1	613	2900	1	613	2900	1 3/4	613	2900	1 3/4	613				
CIRCLING	2900	1	604	2900	1	604	2900	1 3/4	604	2900	2	604				
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WOLF POINT ALTIMETER SETTING AND INCREASE ALL MDA 160 FEET, AND INCREASE S-30 CAT B VISIBILITY 1/4 MILE, CAT C/D VISIBILITY 3/4 MILE, AND CIRCLING CAT B VISIBILITY 1/4 MILE, CAT C VISIBILITY 3/4 MILE, CAT D VISIBILITY 1/2 MILE.																
CITY AND STATE GLASGOW, MT				ELEVATION: 2296 THRE: 2287 AIRPORT NAME: WOKAL FIELD/GLASGOW INTL				FACILITY IDENTIFIER: MKR		PROCEDURE NO./AMD'T NO./EFFECTIVE DATE: NDB RWY 30, AMDT 2 9 FEB 2012				SUP AMDT 1 DATE 02/27/1985		

