

<b>RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
<b>TERMINAL ROUTES</b>								<b>MISSED APPROACH</b>							
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LNAV: RW22  CLIMB TO 3400 DIRECT IZAGI AND HOLD.  <b>ADDITIONAL FLIGHT DATA:</b> HOLD SW, RT, 036.31 INBOUND. CHART FAS OBST: 1739 TREE 380500N/0975032W PAFNA TO RW22: 3.00/42							
HUT VOR/DME		SAYAN (FO)		036.32 / 17.14		3200									
STONS (IAF)		SAYAN (NOPT) (FB)		262.83 / 12.02		3200									
GUTER (IAF)		SAYAN (NOPT) (FB)		149.33 / 6.68		3200									
SAYAN (IF/IAF)		PAFNA (FB)		216.54 / 6.10		3200									
PAFNA (FAF)		RW22 (MAP) (FO)		216.48 / 5.07											
RW22 (MAP)		1943 MSL		216.48											
1943 MSL		IZAGI (FO)				3400									
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. HOLD NE SAYAN, RT, 216.54 INBOUND, 3200 FT. IN LIEU OF PT (IAF) 3. FAC: <u>216.48</u> FAF: <u>PAFNA</u> DIST FAF TO MAP: <u>5.07</u> THLD: <u>5.07</u> 4. MIN. ALT: SAYAN 3200, PAFNA 3200 5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u> 6. MIN GS INCPT: <u>      </u> GS ALT AT: <u>      </u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 7. GS ANGLE: <u>      </u> TCH: <u>34:1</u> IS NOT CLEAR 8. MSA FROM: RW22 4100												MAG VAR: 6E		EPOCH YEAR: 2000	
<b>MINIMUMS</b>															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		STANDARD @							
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	2000	1	457	2000	1	457	2000	1 3/8	457		NA				
CIRCLING	2080	1	537	2080	1	537	2080	1 1/2	537		NA				
<b>NOTES:</b> CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE NEWTON ALTIMETER SETTING AND INCREASE <span style="float: right;">@ NA WHEN LOCAL WEATHER NOT AVAILABLE.</span> ALL MDAS 80 FEET, LNAV CAT C VISIBILITY 1/8 AND CIRCLING CAT C VISIBILITY 1/4 MILE. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. (SEE FORM 8260-10)															
CITY AND STATE  HUTCHINSON, KS				ELEVATION: 1543    THRE: 1543 AIRPORT NAME:  HUTCHINSON MUNI				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, ORIG 13 JAN 2011				SUP: AMDT: NONE DATED	

QUALITY  
2  
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT STONS ON V280 NORTHEAST BOUND AND V532 NORTH AND SOUTHBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON HUT VOR/DME AIRWAY RADIALS 016 CW 069.

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

QUALITY  
2  
CHECKED

CITY AND STATE  
HUTCHINSON, KS

ELEVATION: 1543 THRE: 1543  
AIRPORT NAME:  
HUTCHINSON MUNI

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 22, ORIG  
13 JAN 2011

SUP:  
AMDT: NONE  
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, MAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE  HUTCHINSON, KS	ELEVATION: 1543 THRE: 1543  AIRPORT NAME:  HUTCHINSON MUNI	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  RNAV (GPS) RWY 22, ORIG  13 JAN 2011	SUP:
				AMDT: NONE
				DATED:

## U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3	
RUNWAY	1234567890123456789012345678901234567890123456789012345678901234567890123456789012													
-----														
SUSAP KHUTK3GRW22	0060002164	N38041438W	097505854-0400	+0442101543000042100R										
-----														
	1	2	3	4	5	6	7	8	9	0	1	2	3	
MSA	1234567890123456789012345678901234567890123456789012345678901234567890123456789012													
-----														
SUSAP KHUTK3SRW22 K3PG	0			18018004125										M

CITY AND STATE  
HUTCHINSON, KS

ELEVATION: 1543 THRE: 1543  
AIRPORT NAME:  
HUTCHINSON MUNI

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 22, ORIG  
13 JAN 2011

SUP:  
AMDT: NONE  
DATED: