

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW19R  CLIMB TO 2000 THEN CLIMBING RIGHT TURN TO 2800 DIRECT BAE VORTAC AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD W, RT, 090.00 INBOUND. CHART FAS OBST: 849 TREE 425754N/0875409W CHART: 910 BLDG 425957N/0875319W DISTANCE TO THLD FROM 200 HATH: 0.46 NM. CHART VDP AT 1.11 MILES TO RW19R* *LNAV ONLY. WAAS CHANNEL # 99322 REFERENCE PATH ID: W19A LTP HAE: 169.6 M											
GOMPE (IAF)	ADELE (FB)	099.01 / 11.00	2900												
HAGIN (IAF)	ADELE (FB)	279.35 / 11.00	2900												
ADELE (IF)	OMOG (FB)	189.18 / 7.10	2800												
OMOG (FAF)	BAYZE/2.60 NM TO RW19R (FB)	189.17 / 3.91													
BAYZE/2.60 NM TO RW19R	RW19R (MAP) (FO)	189.17 / 2.60													
RW19R (MAP)	2000 MSL	189.17	2000												
2000 MSL	BAE VORTAC (FO)		2800												
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. PROFILE STARTS AT ADELE 3. FAC: 189.17 FAF: OMOG DIST FAF TO MAP: 6.52 THLD: 6.52 4. MIN. ALT: ADELE 2900, OMOG 2800, BAYZE/2.60 NM TO RW19R 1540* 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: 2800 GS ALT AT: OMOG 2800 OM: MM: IM: 7. GS ANGLE: 3.00 TCH: 54.1 34:1 IS CLEAR 8. MSA FROM: RW19R 2900				MAG VAR: 2W EPOCH YEAR: 1995											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A											
CATEGORY =====>				STANDARD											
	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	871	2400	200	871	2400	200	871	2400	200	871	2400	200			
LNAV/VNAV DA	1030	4000	359	1030	4000	359	1030	4000	359	1030	4000	359			
LNAV MDA	1100	2400	429	1100	2400	429	1100	4000	429	1100	4000	429			
CIRCLING	1240	1	511	1240	1	511	1240	1 1/2	511	1280	2	551			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -22C (-7F) OR ABOVE 39C (102F). CHART NOTE: FOR INOPERATIVE MALSR, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 1/8 MILE. CHART NOTE: DME/DME RNP-0.3 NA. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 729 THRE: 671		FACILITY		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
MILWAUKEE, WI		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 19R, AMDT 2				AMDT: 1					
		GENERAL MITCHELL INTL				20 OCT 2011				DATED 06/30/2011					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):  
CHART PLANVIEW NOTE: RADAR REQUIRED.  
CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

QUALITY  
2  
CHECKED

CITY AND STATE MILWAUKEE, WI	ELEVATION: 729	THRE: 671	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19R, AMDT 2 20 OCT 2011	SUP:
	AIRPORT NAME:				AMDT: 1
	GENERAL MITCHELL INTL				DATED: 06/30/2011

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0  
SBAS SERVICE PROVIDER IDENTIFIER 0  
AIRPORT IDENTIFIER KMKE  
RUNWAY RW19R  
APPROACH PERFORMANCE DESIGNATOR 0  
ROUTE INDICATOR  
REFERENCE PATH DATA SELECTOR 0  
REFERENCE PATH IDENTIFIER (APPROACH ID) W19A  
LTP/FTP LATITUDE 425720.0050N  
LTP/FTP LONGITUDE 0875336.0935W  
LTP/FTP ELLIPSOIDAL HEIGHT +01696  
FPAP LATITUDE 425551.5800N  
FPAP LONGITUDE 0875351.2100W  
THRESHOLD CROSSING HEIGHT (TCH) 00054.1  
TCH UNITS SELECTOR (METERS OR FEET USED) F  
GLIDEPATH ANGLE (GPA) 03.00  
COURSE WIDTH AT THRESHOLD 106.75  
LENGTH OFFSET 0032  
HORIZONTAL ALERT LIMIT (HAL) 40.0  
VERTICAL ALERT LIMIT (VAL) 35.0

CRC REMAINDER

4BBE32CD

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K5  
LTP ORTHOMETRIC HEIGHT +02046  
FPAP ORTHOMETRIC HEIGHT +02046

QUALITY  
2  
CHECKED

CITY AND STATE

MILWAUKEE, WI

ELEVATION: 729

THRE: 671

AIRPORT NAME:

GENERAL MITCHELL INTL

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 19R, AMDT 2

20 OCT 2011

SUP:

AMDT:

1

DATED:

06/30/2011

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY  
4  
3-10

CITY AND STATE MILWAUKEE, WI	ELEVATION: 729 THRE: 671 AIRPORT NAME: GENERAL MITCHELL INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19R, AMDT 2 20 OCT 2011	SUP:
				AMDT: 1
				DATED: 06/30/2011

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

ELEVATION: 729                      THRE: 671  
AIRPORT NAME:  
GENERAL MITCHELL INTL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 19R, AMDT 2  
20 OCT 2011

SUP:	
AMDT:	1
DATED:	06/30/2011