

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW24 CLIMB TO 500 THEN CLIMBING LEFT TURN TO 1700 DIRECT MAJEF AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 205 POLE 701211N/1482725W DISTANCE TO THLD FROM 200 HAT: 0.46 NM. CHART VDP AT 1.08 NM TO RW24* *LNAV ONLY. WAAS CHANNEL # 69203 REFERENCE PATH ID: W24A CHART CIRCLING ICON. LTP HAE: 13.7 M									
UBYEF (IAF)		MAJEF (NOPT) (TF) (FB) (RNP 1.00)			328.65 / 8.00			1700											
QATZA (IAF)		MAJEF (NOPT) (TF) (FB) (RNP 1.00)			148.46 / 8.00			1700											
MAJEF (IF/IAF)		OCOTA (TF) (FB) (RNP 1.00)			238.56 / 7.00			1600											
OCOTA (FAF)		WILIG/2.60 NM TO RW24 (TF) (FB) (RNP 0.30)			238.24 / 2.06														
WILIG/2.60 NM TO RW24 (SEE FORM 8260-10)		RW24 (MAP) (TF) (FO) (RNP 0.30)			238.24 / 2.60														
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NE MAJEF, RT, 238.56 INBOUND, 1700 FT. IN LIEU OF PT (IAF) 3. FAC: 238.24 FAF: OCOTA DIST FAF TO MAP: 4.66 THLD: 4.66 4. MIN. ALT: MAJEF 1700, OCOTA 1600, WILIG/2.60 NM TO RW24 940* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1600 GS ALT AT: OCOTA 1600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 54.0 34:1 IS CLEAR 8. MSA FROM: _____																MAG VAR: 17E		EPOCH YEAR: 2020	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD										
CATEGORY ==>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	266	2400	200	266	2400	200	266	2400	200	266	2400	200	266	2400	200				
LNAV/VNAV DA	381	3000	315	381	3000	315	381	3000	315	381	3000	315	381	3000	315				
LNAV MDA	460	2400	394	460	2400	394	460	3500	394	460	3500	394	460	3500	394				
CIRCLING																			
	540	1	473	540	1	473	580	1 1/2	513	620	2	553	620	2	553				
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE FOR INOPERATIVE ALS, INCREASE LPV CAT E VISIBIITY TO RVR 4000, LNAV/VNAV ALL CATS VISIBILITY TO RVR 5000, AND LNAV CAT E VISIBILITY TO RVR 6000. (CONTINUED ON PAGE 2)																			
CITY AND STATE DEADHORSE, AK		ELEVATION: 67 TDZE: 66 AIRPORT NAME: DEADHORSE			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Z RWY 24, AMDT 2, 10/12/7017					SUP: RNAV (GPS) Y RWY 23 AMDT: 1C DATED 05/29/2014							

QUALITY
 4
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW24 (MAP)	500 MSL (CA)	238.24	500
500 MSL	MAJEF (DF) (FO) (RNP 1.00)		1700

NOTES, (CONT.):

CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA.

TAA

	FROM	TO	ALT
1.	149/30 CW 329/30 (NOPT)	149/10 CW 329/10	2500
2.	149/10 CW 329/10	MAJEF (IF/IAF) (FB)	1700
3.	329/30 CW 059/30	UBYEF (IAF) (FB)	2500
4.	059/30 CW 149/30	QATZA (IAF) (FB)	2500

QUALITY
4
CHECKED

CITY AND STATE
DEADHORSE, AK

ELEVATION: 67 TDZE: 66
AIRPORT NAME:
DEADHORSE

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) Z RWY 24, AMDT 2, 10/12/2017

SUP: RNAV (GPS) Y RWY 23
AMDT: 1C
DATED: 05/29/2014

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE DEADHORSE, AK	ELEVATION: 67 TDZE: 66 AIRPORT NAME: DEADHORSE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Z RWY 24, AMDT 2, 10/12/2017	SUP: RNAV (GPS) Y RWY 23
				AMDT: 1C
				DATED: 05/29/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	PASC
RUNWAY	RW24
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Z
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W24A
LTP/FTP LATITUDE	701149.3815N
LTP/FTP LONGITUDE	1482623.5370W
LTP/FTP ELLIPSOIDAL HEIGHT	+00137
FPAP LATITUDE	701126.4155N
FPAP LONGITUDE	1483036.3280W
THRESHOLD CROSSING HEIGHT (TCH)	00054.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0768
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

BA12525E

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	PA
LTP ORTHOMETRIC HEIGHT	+00185
FPAP ORTHOMETRIC HEIGHT	+00185

QUALITY
4
CHECKED

CITY AND STATE DEADHORSE, AK	ELEVATION: 67 AIRPORT NAME: DEADHORSE	TDZE: 66	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Z RWY 24, AMDT 2, 10/12/2017	SUP: RNAV (GPS) Y RWY 23
					AMDT: 1C
					DATED: 05/29/2014