

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: SCC VOR/DME					
SCC VOR/DME		OCOTA/SCC 4.16 DME		058.06 / 4.16				1600		CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 2000 DIRECT SCC VOR/DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 2000. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 238.06 INBOUND. CHART FAS OBST: 222 RIG 701259N/1482455W CHART VDP AT 0.64 DME DISTANCE VDP TO THLD 1.14 NM. CHART SCC R-278 AT YIGUF. CHART SCC R-184 AT SHELO. CHART SCC R-163 AT ARCON. CHART SCC R-144 AT UVALL. CHART CIRCLING ICON. OCOTA TO RW24: 3.00/54. CHART PLANVIEW NOTE: DME REQUIRED.					
YIGUF/SCC 16.00 DME CW (IAF)		QUVQU/SCC 16.00 DME (NOPT)		16.00 DME ARC (SCC LR-050)				2300							
SHELO/SCC 16.00 DME CCW (IAF)		QUVQU/SCC 16.00 DME (NOPT)		16.00 DME ARC (SCC LR-066)				2300							
ARCON/SCC 16.00 DME CCW (IAF)		QUVQU/SCC 16.00 DME (NOPT)		16.00 DME ARC (SCC LR-066)				2300							
UVALL/SCC 16.00 DME CCW (IAF)		QUVQU/SCC 16.00 DME (NOPT)		16.00 DME ARC (SCC LR-066)				2300							
QUVQU/SCC 16.00 DME (IF)		OCOTA/SCC 4.16 DME		238.06 / 11.84 (SCC R-058)				1600							
1. PT <u> L </u> SIDE OF COURSE <u> 058.06 </u> OUTBOUND <u> 1600 </u> FT WITHIN <u> 15 </u> MILES OF <u> OCOTA </u> (IAF) 2. _____ 3. FAC <u> 238.06 </u> FAF <u> OCOTA/SCC 4.16 DME </u> DIST FAF TO MAP _____ THLD <u> 4.66 </u> 4. MIN. ALT <u> OCOTA 1600, WILIG/SCC 2.10 DME 940 </u> 8. MSA FROM: <u> SCC VOR/DME 2200 </u>															
										MAG VAR: 17E		EPOCH YEAR: 2020			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-24	480	2400	414	480	2400	414	480	4000	414	480	4000	414	480	4000	414
CIRCLING	540	1	473	540	1	473	580	1 1/2	513	620	2	553	620	2	553
NOTES: CHART NOTE: DME REQUIRED. CHART NOTE: FOR INOPERATIVE ALS, INCREASE CATS C/D/E VISIBILITY TO RVR 6000.															
CITY AND STATE		ELEVATION: 67		TDZE: 66		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP VOR/DME RWY 23			
DEADHORSE, AK		AIRPORT NAME:		DEADHORSE		SCC		VOR Z RWY 24, AMDT 5, 10/12/2017				AMDT 4A			
												DATE 05/29/2014			



**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
18
CHECKED

CITY AND STATE

DEADHORSE, AK

ELEVATION: 67

TDZE: 66

AIRPORT NAME:

DEADHORSE

FACILITY
IDENTIFIER:

SCC

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR Z RWY 24, AMDT 5, 10/12/2017

SUP: VOR/DME RWY 23

AMDT: 4A

DATED: 05/29/2014