

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES								MISSED APPROACH				
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LP: RW30L LNAV: RW30L CLIMB TO 4300 DIRECT GEJRI AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 122.47 INBOUND. CHART FAS OBST: 1434 TREE 331646N/1113805W CHART FAS OBST: 1444 TREE 331628N/1113429W CHART R-2310A, R-2310B, R-2310C. WAAS CHANNEL #93525 REFERENCE PATH ID: W30B AKYIV TO RW30L: 3.00/55. CHART VDP AT 1.17 MILES TO RW30L 1699 AAO 331457N/1113343W LTP HAE: 389 M				
TOTEC		BBALL (FB)		029.78 / 11.36		4000						
BBALL (IAF)		SEZUW (FB)		345.46 / 11.97		4000						
SEZUW (IF)		AKYIV (FB)		302.65 / 6.10		3000						
AKYIV (FAF)		OPUYE/1.80 NM TO RW30L (FB)		302.61 / 3.13								
OPUYE/1.80 NM TO RW30L		RW30L (MAP) (FO)		302.58 / 1.80								
RW30L (MAP)		1782 MSL		302.58		4300						
1782 MSL		GEJRI (FO)										
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT SEZUW 3. FAC: <u>302.61</u> FAF: <u>AKYIV</u> DIST FAF TO MAP: <u>4.93</u> THLD: <u>4.93</u> 4. MIN. ALT: <u>SEZUW 4000, AKYIV 3000, OPUYE/1.80 NM TO RW30L 2000</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCTP: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u>34:1 IS CLEAR</u> 8. MSA FROM: <u>RW30L 8900</u>								MAG VAR: 13E EPOCH YEAR: 1980				
MINIMUMS												
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		STANDARD @				
CATEGORY ==>		A		B		C		D		E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	1800	1	427	1800	1	427	1800	1 1/4	427	1800	1 1/4	427
LNAV MDA	1800	1	427	1800	1	427	1800	1 1/4	427	1800	1 1/4	427
CIRCLING	1800	1	418	1840	1	458	1840	1 1/2	458	1940	2	558
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PHOENIX SKY HARBOR INTL ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET; INCREASE LP AND LNAV CAT C, D AND E VISIBILITY 1/8 MILE AND CIRCLING CAT E VISIBILITY 1/4 MILE. (SEE FORM 8260-10)												
CITY AND STATE PHOENIX, AZ		ELEVATION: 1382 THRE: 1373 AIRPORT NAME: PHOENIX-MESA GATEWAY		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 30L, AMDT 1 15 DEC 2011				SUP: AMDT: ORIG-A DATED 03/12/2009		

QUALITY
2
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: VDP NA WITH PHOENIX SKY HARBOR INTL ALTIMETER SETTING.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT TOTEC ON V94 WESTBOUND AND V16 SOUTHEAST BOUND.

QUALITY
2
CHECKED

CITY AND STATE PHOENIX, AZ	ELEVATION: 1382	THRE: 1373	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 30L, AMDT 1 15 DEC 2011	SUP:
	AIRPORT NAME: PHOENIX-MESA GATEWAY				AMDT: ORIG-A
					DATED: 03/12/2009

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KIWA
RUNWAY RW30L
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W30B
LTP/FTP LATITUDE 331750.1420N
LTP/FTP LONGITUDE 1113856.5360W
LTP/FTP ELLIPSOIDAL HEIGHT +03890
FPAP LATITUDE 331903.6140N
FPAP LONGITUDE 1114022.3230W
THRESHOLD CROSSING HEIGHT (TCH) 00055.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 0000
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 0.0

CRC REMAINDER

C4B93350

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K2
LTP ORTHOMETRIC HEIGHT +04186
FPAP ORTHOMETRIC HEIGHT +04186

QUALITY
2
CHECKED

CITY AND STATE

PHOENIX, AZ

ELEVATION: 1382

THRE: 1373

AIRPORT NAME:

PHOENIX-MESA GATEWAY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 30L, AMDT 1

15 DEC 2011

SUP:

AMDT: ORIG-A

DATED: 03/12/2009

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE PHOENIX, AZ	ELEVATION: 1382 THRE: 1373 AIRPORT NAME: PHOENIX-MESA GATEWAY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 30L, AMDT 1 15 DEC 2011	SUP:
				AMDT: ORIG-A
				DATED: 03/12/2009

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP	KIWAK2PR30L	RW30L002E	+04186+04186LP	93525
-------	-------------	-----------	----------------	-------

[illegible]

QUALITY
1
CHECKED

ELEVATION: 1382 THRE: 1373
AIRPORT NAME:
 PHOENIX-MESA GATEWAY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 30L, AMDT 1
15 DEC 2011

SUP:	
AMDT:	ORIG-A
DATED:	03/12/2009