

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION															
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW19 LNAV: RW19 CLIMBING RIGHT TURN TO 3000 DIRECT JUTEK AND HOLD. ADDITIONAL FLIGHT DATA: HOLD W, RT, 095.35 INBOUND. CHART FAS OBST: 459 TREE 445715N/0730517W FAS OBST: 399 AAO 445829N/0730637W WAAS CHANNEL # 78122 REFERENCE PATH ID: W19A DUCED TO RW19: 3.00/45 LTP HAE: 40.2 M											
WARDS	UPEDE (FO)	038.03 / 5.74	1800												
YJN VORTAC (IAF)	UPEDE (NOPT) (FB)	155.86 / 11.93	1800												
UPEDE (IF/IAF)	DUCED (FB)	185.44 / 4.93	1800												
DUCED (FAF)	RW19 (MAP) (FO)	185.46 / 4.80													
RW19 (MAP)	628 MSL	185.46													
628 MSL	JUTEK (FO)		3000												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N UPEDE, RT, 185.44 INBOUND, 1800 FT. IN LIEU OF PT (IAF) 3. FAC: 185.46 FAF: DUCED _____ DIST FAF TO MAP: 4.80 THLD: 4.80 4. MIN. ALT: UPEDE 1800, DUCED 1800 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW19 5600				MAG VAR: 16W EPOCH YEAR: 1995											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @									
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	660	1	432	660	1	432		NA			NA				
LNAV MDA	720	1	492	720	1	492		NA			NA				
CIRCLING	780	1	552	820	1	592		NA			NA				
NOTES: CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 1 NA AT NIGHT. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: STRAIGHT-IN/CIRCLING RWY 19 PROCEDURE NA AT NIGHT. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 228 THRE: 228		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
HIGHGATE, VT		AIRPORT NAME:		FRANKLIN COUNTY STATE		RNAV (GPS) RWY 19, AMDT 1				AMDT: ORIG-A					
						30 JUN 2011				DATED 09/23/2010					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PLATTSBURGH ALTIMETER SETTING AND INCREASE ALL MDA 60 FT.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON YJN VORTAC AIRWAY RADIALS 084 CW 102.

CITY AND STATE
HIGHGATE, VT

ELEVATION: 228 THRE: 228
AIRPORT NAME:
FRANKLIN COUNTY STATE

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 19, AMDT 1
30 JUN 2011

SUP:
AMDT: ORIG-A
DATED: 09/23/2010

QUALITY
2
CHECKED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KFSO
RUNWAY	RW19
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	W19A
REFERENCE PATH IDENTIFIER (APPROACH ID)	445639.5700N
LTP/FTP LATITUDE	0730554.6700W
LTP/FTP LONGITUDE	+00402
LTP/FTP ELLIPSOIDAL HEIGHT	445511.9800N
FPAP LATITUDE	0730531.7500W
FPAP LONGITUDE	00045.0
THRESHOLD CROSSING HEIGHT (TCH)	F
TCH UNITS SELECTOR (METERS OR FEET USED)	03.00
GLIDEPATH ANGLE (GPA)	106.75
COURSE WIDTH AT THRESHOLD	1832
LENGTH OFFSET	40.0
HORIZONTAL ALERT LIMIT (HAL)	0.0
VERTICAL ALERT LIMIT (VAL)	

CRC REMAINDER B10E48DB

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+00694
FPAP ORTHOMETRIC HEIGHT	+00694

QUALITY
2
CHECKED

CITY AND STATE HIGHGATE, VT	ELEVATION: 228 THRE: 228 AIRPORT NAME: FRANKLIN COUNTY STATE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, AMDT 1 30 JUN 2011	SUP: AMDT: ORIG-A DATED: 09/23/2010
--------------------------------	---	---------------------------------	--	---

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE HIGHGATE, VT	ELEVATION: 228 THRE: 228 AIRPORT NAME: FRANKLIN COUNTY STATE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, AMDT 1 30 JUN 2011	SUP:	
				AMDT:	ORIG-A
				DATED:	09/23/2010

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
PP	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KFSOK6PR19	RW19 001	0000W19A0N4456395700W07305546700+004020300N4455119800W07305317500106751832000450F400000B10E48DB										
	SUSAP KFSOK6PR19	RW19 002E	+00694+00694LP	78122									

	1	2	3	4	5	6	7	8	9	0	1	2	3
MSA	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KFSOK6SRW19 K6PG		0	18018005625								M	

QUALITY
&
CHECKED

CITY AND STATE

HIGHGATE, VT

ELEVATION: 228

THRE: 228

AIRPORT NAME:

FRANKLIN COUNTY STATE

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 19, AMDT 1

30 JUN 2011

SUP:

AMDT: ORIG-A

DATED: 09/23/2010