

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: ENA 3.58 DME FIX							
ENA VOR/DME		DIXIT/ENA 10.00 DME			192.08 / 10.00			2200		CLIMB TO 2000 DIRECT ENA VOR/DME AND ON ENA VOR/DME R-028 TO SWANS/ENA 10.00 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 207.87 INBOUND. CHART FAS OBST: 223 TOWER 603401N/1511631W CHART (CFVKC) AT INTERSECTION OF BEYAY DR LEG AND INTERMEDIATE COURSE. CHART ENA R-220 AT ACIGE. CHART VDP AT 4.64 DME. DISTANCE VDP TO THLD 1.05 MILES DIXIT TO RW01L: 3.02/53 CHART CIRCLING ICON							
ACIGE/ENA 20.00 DME CCW (IAF)		JASGO/ENA 20.00 DME (NOPT)			20.00 DME ARC			2200									
BEYAY/ENA 24.00 DME (IAF)		JASGO/ENA 20.00 DME (NOPT)			062.00 / 3.36 (HDG) & 012.08 / 1.70 (ENA R-192)			2200									
HOM VOR/DME (IAF)		EKAYU/HOM 20.00 DME			332.12 / 20.00			3500									
EKAYU/HOM 20.00 DME		JASGO/ENA 20.00 DME (NOPT)			332.12 / 17.39 (HOM R-332)			2200									
JASGO/ENA 20.00 DME (IF)		DIXIT/ENA 10.00 DME			012.08 / 10.00 (ENA R-192)			2200									
1. PT <u> R </u> SIDE OF COURSE <u> 192.08 </u> OUTBOUND <u> 2200 </u> FT WITHIN <u> 10 </u> MILES OF <u> DIXIT </u> (IAF) 2. _____ 3. FAC <u> 012.08 </u> FAF <u> DIXIT/ENA 10.00 DME </u> DIST FAF TO MAP _____ THLD <u> 6.42 </u> 4. MIN. ALT <u> DIXIT 2200, DOKKA/ENA 6.00 DME 900 </u> 8. MSA FROM: <u> ENA VOR/DME 030-210 3500, 210-030 2200 </u>														MAG VAR: 19E		EPOCH YEAR: 2010	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-02L	480	1	386	480	1	386	480	1 1/8	386	480	1 1/8	386					
CIRCLING	560	1	460	580	1	480	580	1 1/2	480	740	2	640					
NOTES: CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HOM VOR/DME ON V438 SOUTHBOUND. @ NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SOLDOTNA ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET; INCREASE S-2L CAT C AND D VISIBILITY 1/8 MILE AND CIRCLING CAT D VISIBILITY 1/4 MILE. (CONTINUED ON PAGE 2)																	
CITY AND STATE		ELEVATION: 100			TDZE: 94			FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP VOR/DME RWY 1L				
KENAI, AK		AIRPORT NAME:			KENAI MUNI			ENA		VOR/DME RWY 2L, AMDT 9 10 DECEMBER 2015			AMDT 8A				
													DATE 11/13/2014				



**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: NIGHT LANDING: RWY 02R, 20L NA.

CHART NOTE: VDP NA WITH SOLDOTNA ALTIMETER SETTING.

QUALITY
22
CHECKED

CITY AND STATE

KENAI, AK

ELEVATION: 100

TDZE: 94

AIRPORT NAME:

KENAI MUNI

FACILITY
IDENTIFIER:

ENA

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR/DME RWY 2L, AMDT 9

10 DECEMBER 2015

SUP: VOR/DME RWY 1L

AMDT: 8A

DATED: 11/13/2014