

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION	RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33
Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
CUSIB (IAF)	YEJWO (NOPT) (FB)	346.69 / 5.50	2000	LPV: DA LNAV/VNAV: DA LNAV: RW26 CLIMB TO 2000 DIRECT UDAQI AND HOLD.
ZIXIL (IAF)	YEJWO (NOPT) (FB)	166.65 / 5.50	2000	
YEJWO (IF/IAF)	WOQTA (FB)	256.67 / 6.68	1600	
WOQTA (FAF)	ZALDU/2.10 NM TO RW26 (FB)	256.60 / 2.69		ADDITIONAL FLIGHT DATA: HOLD W, RT, 076.43 INBOUND. CHART FAS OBST: 125 TREE 303034N/0814010W CHART: 150 TOWER 303106N/0813758W CHART MAYPORT LOW/HIG MOA. DISTANCE TO THLD FROM 200 HATH: 0.47 NM. CHART VDP AT 0.89 MILES TO RW26*
ZALDU/2.10 NM TO RW26	RW26 (MAP) (FO)	256.60 / 2.10		
RW26 (MAP)	226 MSL	256.60		
226 MSL	UDAQI (FO)		2000	

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)	
2. HOLD E YEJWO, RT, 256.67 INBOUND, 2000 FT. IN LIEU OF PT (IAF)	
3. FAC: <u>256.60</u> FAF: <u>WOQTA</u>	DIST FAF TO MAP: <u>4.79</u> THLD: <u>4.79</u>
4. MIN. ALT: YEJWO 2000, WOQTA 1600, ZALDU/2.10 NM TO RW26 740*	
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>	
6. MIN GS INCPT: <u>1600</u> GS ALT AT: WOQTA 1600 OM: <u> </u> MM: <u> </u> IM: <u> </u>	
7. GS ANGLE: <u>3.00</u> TCH: <u>48.7</u> 34:1 IS CLEAR	
8. MSA FROM: <u> </u>	
MAG VAR: 6W EPOCH YEAR: 2010	

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD						
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	226	2400	200	226	2400	200	226	2400	200	226	2400	200			
LNAV/VNAV DA	296	2400	270	296	2400	270	296	2400	270	296	2400	270			
LNAV MDA	380	2400	354	380	2400	354	380	3000	354	380	3000	354			
CIRCLING	520	1	491	520	1	491	520	1 1/2	491	640	2	611			

NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -5C (23F) OR ABOVE 54C (130F). CHART NOTE: FOR INOPERATIVE MALSR, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO RVR 4500 AND INCREASE LNAV CATS C/D VISIBILITY TO RVR 5000. CHART NOTE: DME/DME RNP-0.3 NA. (SEE FORM 8260-10)					
CITY AND STATE	ELEVATION: 29 THRE: 26	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 26	
JACKSONVILLE, FL	AIRPORT NAME: JACKSONVILLE INTL		RNAV (GPS) Z RWY 26, AMDT 2 10 JANUARY 2013	AMDT: 1	
				DATED 12/15/2011	

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE AT ZIXIL : MAX 210 KIAS.

CHART PLANVIEW NOTE AT CUSIB : MAX 210 KIAS.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

TAA

	FROM	TO	ALT
1.	167/30 CW 347/30 (NOPT)	YEJWO (IF/IAF) (FB)	2000
2.	347/30 CW 257/30	CUSIB (IAF) (FB)	2100
3.	257/30 CW 167/30	ZIXIL (IAF) (FB)	2700

QUALITY
CHECKED

CITY AND STATE
JACKSONVILLE, FL

ELEVATION: 29 THRE: 26
AIRPORT NAME:
JACKSONVILLE INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) Z RWY 26, AMDT 2
10 JANUARY 2013

SUP: RNAV (GPS) RWY 26
AMDT: 1
DATED: 12/15/2011

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KJAX
RUNWAY RW26
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR Z
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W26A
LTP/FTP LATITUDE 303019.3405N
LTP/FTP LONGITUDE 0814012.0970W
LTP/FTP ELLIPSOIDAL HEIGHT -00203
FPAP LATITUDE 302946.3900N
FPAP LONGITUDE 0814159.8800W
THRESHOLD CROSSING HEIGHT (TCH) 00048.7
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 0000
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 35.0

CRC REMAINDER

00D5BAAA

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K7
LTP ORTHOMETRIC HEIGHT +00080
FPAP ORTHOMETRIC HEIGHT +00080

QUALITY
CHECKED

CITY AND STATE JACKSONVILLE, FL	ELEVATION: 29 THRE: 26	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Z RWY 26, AMDT 2 10 JANUARY 2013	SUP: RNAV (GPS) RWY 26
	AIRPORT NAME: JACKSONVILLE INTL			AMDT: 1
				DATED: 12/15/2011

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KJAXK7FR26-Z	ACUSIB	010CUSIBK7EA0E	A	IF					18000210		A-JS	
SUSAP	KJAXK7FR26-Z	ACUSIB	020YEJWOK7EA0EE	B	010TF		34670055	+	02000			A JS	
SUSAP	KJAXK7FR26-Z	AYEJWO	010YEJWOK7EA0EE	AR	HF		25670040	+	02000	18000		A JS	
SUSAP	KJAXK7FR26-Z	AZIXIL	010ZIXILK7EA0E	A	IF					18000210		A-JS	
SUSAP	KJAXK7FR26-Z	AZIXIL	020YEJWOK7EA0EE	B	010TF		16670055	+	02000			A JS	
SUSAP	KJAXK7FR26-Z	R	010YEJWOK7EA0E	I	IF			+	02000	18000		A JS	
SUSAP	KJAXK7FR26-Z	R	020WOQTAK7EA1E	F	051TF		25670067	+	01600			A JS	
SUSAP	KJAXK7FR26-Z	R	020WOQTAK7EA2WALPV			ALNAV/VNAV	ALNAV					JS	
SUSAP	KJAXK7FR26-Z	R	021ZALDUK7EA0E	S	031TF		25660027	V	0074000750	-300		A JS	
SUSAP	KJAXK7FR26-Z	R	030RW26 K7PGOGY M	031TF			25660021		00075	-300		A JS	
SUSAP	KJAXK7FR26-Z	R	040	0	M	CA	2566	+	00226			A JS	
SUSAP	KJAXK7FR26-Z	R	050UDAQIK7EA0EY		DF			+	02000			A JS	
SUSAP	KJAXK7FR26-Z	R	060UDAQIK7EA0EE	R	HM		07640040	+	02000			A JS	

[illegible][illegible]

QUALITY
4
CHECKED

FAA FORM 8260 - 10 / April 2006 (Computer Generated)

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	CUSIB	CUSIB	010	IAF	IF		FB					AB 210
	CUSIB	YEJWO	020		TF		FB	1.0	346.7(340.7T)	005.5	AA 02000	
	YEJWO	YEJWO	010	IAF	HF	R	FO		256.7(250.7T)	004.0	AA 02000	
	ZIXIL	ZIXIL	010	IAF	IF		FB					AB 210
	ZIXIL	YEJWO	020		TF		FB	1.0	166.7(160.7T)	005.5	AA 02000	
		YEJWO	010	FACF	IF		FB				AA 02000	
		WOQTA	020	FAF	TF		FB	0.5	256.7(250.7T)	006.7	AA 01600	
		ZALDU	021	SDF	TF		FB	0.3	256.6(250.6T)	002.7	AA 00740	GS 00750
		RW26	030	MAP	TF		FO	0.3	256.6(250.6T)	002.1	AT 00075	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		256.6(250.6T)		AA 00226	
	UDAI	050		DF		FO				AA 02000	
	UDAI	060		HM	R	FO		076.4(070.4T)	004.0	AA 02000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CUSIB	N302856.16	W0812534.01	N3028.936	W08125.567
	UDAI	N302536.40	W0815533.99	N3025.607	W08155.567
	WOQTA	N303155.09	W0813458.35	N3031.918	W08134.973
	YEJWO	N303408.30	W0812740.43	N3034.138	W08127.674
	ZALDU	N303101.35	W0813754.54	N3031.023	W08137.909
	ZIXIL	N303920.40	W0812947.07	N3039.340	W08129.785
	RW26	N303019.34	W0814012.10	N3030.322	W08140.202

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW26	00026	49



CITY AND STATE JACKSONVILLE, FL	ELEVATION: 29	THRE: 26	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 26
	AIRPORT NAME: JACKSONVILLE INTL		RNAV	RNAV (GPS) Z RWY 26, AMDT 2	AMDT: 1
				10 JANUARY 2013	DATED: 12/15/2011