

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

TYPE: SID

DP ROUTE DESCRIPTION:

CHARLOTTE/DOUGLAS INTL: RWY 5: CLIMB HEADING 055.47, THENCE... **RWY 18R:** CLIMBING RIGHT TURN HEADING 200, THENCE... **RWY 18C:** CLIMB HEADING 182.96 UNTIL PASSING CLT VOR/DME 1.6 DME, THEN TURN RIGHT HEADING 200, THENCE... **RWY 18L:** CLIMB HEADING 182.97, THENCE... **RWY 23:** CLIMB HEADING 235.48, THENCE... **RWY 36L:** CLIMBING LEFT TURN HEADING 315, THENCE... **RWY 36C:** CLIMBING LEFT TURN HEADING 330, THENCE... **RWY 36R:** CLIMBING RIGHT TURN HEADING 025, THENCE...
...EXPECT RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 8000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

CONCORD RGNL: RWY 2: CLIMB HEADING 016.46, THENCE... **RWY 20:** CLIMBING LEFT TURN HEADING 150, THENCE...
...EXPECT RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

GASTONIA MUNI: RWY 3: CLIMB HEADING 034.34, THENCE... **RWY 21:** CLIMB HEADING 214.33, THENCE...
...EXPECT RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3400, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

CHARLOTTE-MONROE EXECUTIVE: RWY 5: CLIMB HEADING 053.00, THENCE... **RWY 23:** CLIMB HEADING 233.00, THENCE...
...EXPECT RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

ROCK HILL/YORK CO/BRYANT FIELD: RWY 2: CLIMB HEADING 016.22, THENCE... **RWY 20:** CLIMB HEADING 196.22, THENCE...
...EXPECT RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

LINCOLN-TON-LINCOLN COUNTY RGNL: RWY 5: CLIMB HEADING 063.15 TO 2000 BEFORE PROCEEDING ON COURSE, THENCE... **RWY 23:** CLIMB HEADING 233.15 TO 2800 BEFORE TURNING LEFT, THENCE...
...EXPECT RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

LANCASTER COUNTY-MC WHIRTER FIELD: RWY 6, CLIMB HEADING 065.51, THENCE... **RWY 24,** CLIMB HEADING 245.52, THENCE...
...EXPECT RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

STANLY COUNTY: RWY 4R, CLIMB HEADING 043.18, THENCE... **RWY 22L,** CLIMB HEADING 223.19, THENCE...
...EXPECT RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

ROWAN COUNTY: RWY 2, CLIMB HEADING 021.99, THENCE... **RWY 20,** CLIMB HEADING 160.00 TO 1500 BEFORE TURNING WEST, THENCE...
...EXPECT RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	Crossing Altitudes/Fixes
HARAY	BOB6.HARAY	CLT VOR/DME	HARAY	270.00 (CLT R-270)	40.00	14000	2900	
ZAVR	BOB6.ZAVR	CLT VOR/DME	HARAY	270.00 (CLT R-270)	40.00	14000	2900	
		HARAY	ZAVR	270.00 (CLT R-270)	25.00	14000	5700	
DEBIE	BOB6.DEBIE	CLT VOR/DME	DEBIE	255.00 (CLT R-255)	45.00	14000	2600	

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

NOTE: FOR TURBOJETTS ONLY. **NOTE:** RADAR AND DME REQUIRED. **NOTE (CHARLOTTE/DOUGLAS INTL ONLY):** TRANSPONDER CODE WILL BE ISSUED VIA PDC OR CHARLOTTE CLEARANCE DELIVERY. **NOTE (CONCORD RGNL ONLY):** TRANSPONDER CODE WILL BE ISSUED VIA CONCORD ATCT OR CHARLOTTE CLEARANCE DELIVERY.



U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
 Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

NOTE (GASTONIA MUNI, CHARLOTTE-MONROE EXECUTIVE, ROCK HILL/YORK CO/BRYANT FIELD, LINCOLNTON-LINCOLN COUNTY RGNL, LANCASTER COUNTY-MC WHIRTER FIELD, STANLY COUNTY, ROWAN COUNTY ONLY): TRANSPONDER CODE WILL BE ISSUED VIA CHARLOTTE CLEARANCE DELIVERY.

TAKEOFF MINIMUMS: CHARLOTTE/DOUGLAS INTL: RWY 5, 18R, 18L, 18C, 23, 36R, 36C, STANDARD. RWY 36L: STANDARD WITH MINIMUM CLIMB OF 215 FT PER NM TO 3500.

CONCORD RGNL: RWY 2, STANDARD. RWY 20, STANDARD WITH MINIMUM CLIMB OF 318 FT PER NM TO 2400.

GASTONIA MUNI: RWY 3, 21, STANDARD.

CHARLOTTE-MONROE EXECUTIVE: RWY 5, 23, STANDARD.

ROCK HILL/YORK CO/ BRYANT FIELD: RWY 2, 20, STANDARD.

LINCOLNTON-LINCOLN COUNTY RGNL: RWY 5, STANDARD WITH MINIMUM ATC CLIMB OF 250 FT PER NM TO 3000. RWY 23, STANDARD WITH MINIMUM ATC CLIMB OF 250 FT PER NM TO 3000. IF UNABLE TO ACCEPT CLIMB RATE, ADVISE ATC ON INITIAL CONTACT.

LANCASTER COUNTY-MC WHIRTER FIELD: RWY 6, STANDARD WITH MINIMUM ATC CLIMB OF 250 FT PER NM TO 3000. RWY 24, STANDARD WITH MINIMUM ATC CLIMB OF 250 FT PER NM TO 3000. IF UNABLE TO ACCEPT CLIMB RATE, ADVISE ATC ON INITIAL CONTACT.

STANLY COUNTY: RWY 4L, 22R, NA – VFR RUNWAY. RWY 22L, STANDARD WITH MINIMUM ATC CLIMB OF 250 FT PER NM TO 3000. RWY 4R, 300 – 1 ½ OR STANDARD WITH MINIMUM CLIMB OF 276 FT PER NM TO 1000. MINIMUM ATC CLIMB OF 250 FT PER NM TO 3000. IF UNABLE TO ACCEPT CLIMB RATE, ADVISE ATC ON INITIAL CONTACT.

ROWAN COUNTY: RWY 2, STANDARD WITH MINIMUM ATC CLIMB OF 250 FT PER NM TO 3000. RWY 20, 400 – 2 ¾ OR STANDARD WITH MINIMUM CLIMB OF 204 FT PER NM TO 1300, OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT PER NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1300 FT PRIOR TO DEPARTURE END OF RUNWAY. MINIMUM ATC CLIMB OF 250 FT PER NM TO 3000. IF UNABLE TO ACCEPT CLIMB RATE, ADVISE ATC ON INITIAL CONTACT.

TAKEOFF OBSTACLES NOTES:

CHARLOTTE/DOUGLAS INTL: NOTE: RWY 5, TREES BEGINNING 1031 FT FROM DER, 480 FT LEFT OF CENTERLINE, UP TO 127 FT AGL/856 FT MSL. NOTE: RWY 18L, TOWER AND POLE BEGINNING 981 FT FROM DER, 708 FT LEFT OF CENTERLINE, UP TO 160 FT AGL/850 FT MSL. TREES BEGINNING 1235 FT FROM DER, 707 FT RIGHT OF CENTERLINE, UP TO 88 FT AGL/767 FT MSL. NOTE: RWY 18C, TREES BEGINNING 1688 FT FROM DER, 735 FT LEFT OF CENTERLINE, UP TO 108 FT AGL/787 FT MSL. TREES BEGINNING 3251 FT FROM DER, 995 FT RIGHT OF CENTERLINE, UP TO 102 FT AGL/841 FT MSL. NOTE: RWY 23, TREES BEGINNING 3899 FT FROM DER, 216 FT LEFT OF CENTERLINE, UP TO 99 FT AGL/818 FT MSL. TREES BEGINNING 1491 FT FROM DER, 603 FT RIGHT OF CENTERLINE, UP TO 74 FT AGL/823 FT MSL. NOTE: RWY 36C, TREES BEGINNING 1937 FT FROM DER, 725 FT LEFT OF CENTERLINE, UP TO 54 FT AGL/823 FT MSL. TREES BEGINNING 1420 FT FROM DER, 309 FT RIGHT OF CENTERLINE, UP TO 114 FT AGL/823 FT MSL. NOTE: RWY 36R, POLE AND TREES BEGINNING 713 FT FROM DER, 416 FT LEFT OF CENTERLINE, UP TO 94 FT AGL/853 FT MSL. RAILROAD, ANTENNA, POLES, AND TREES BEGINNING 471 FT FROM DER, 93 FT RIGHT OF CENTERLINE, UP TO 93 FT AGL/852 FT MSL.

CONCORD RGNL: NOTE: RWY 2, POLES AND TREES BEGINNING 2624 FT FROM DER, 688 FT LEFT OF CENTERLINE, UP TO 45 FT AGL/784 FT MSL. TREES BEGINNING 2107 FT FROM DER, 787 FT RIGHT OF CENTERLINE, UP TO 24 FT AGL/783 FT MSL. NOTE: RWY 20, STREET LIGHTS BEGINNING 3047 FT FROM DER, 196 FT RIGHT OF CENTERLINE, UP TO 105 FT AGL/744 FT MSL. TREES 1.3 NM FROM DER, 1544 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/849 FT MSL.

GASTONIA MUNI: NOTE: RWY 3, TREES BEGINNING 1200 FT FROM DER, 433 FT LEFT OF CENTERLINE, UP TO 80 FT AGL/859 FT MSL. TREES BEGINNING 162 FT FROM DER, 371 FT RIGHT OF CENTERLINE, UP TO 136 FT AGL/885 FT MSL. NOTE: RWY 21, ANTENNA AND TREES BEGINNING 269 FT FROM DER, 210 FT LEFT OF CENTERLINE, UP TO 101 FT AGL/880 FT MSL. TREES BEGINNING 252 FT FROM DER, 264 FT RIGHT OF CENTERLINE, UP TO 113 FT AGL/882 FT MSL.

CHARLOTTE-MONROE EXECUTIVE: NOTE: RWY 5, TREES BEGINNING 150 FT FROM DER, 202 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/799 FT MSL. VEHICLES ON ROAD AND TREES BEGINNING 199 FT FROM DER, 259 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/789 FT MSL.

ROCK HILL/YORK CO/BRYANT FIELD: NOTE: RWY 2, TREES BEGINNING 99 FT FROM DER, 174 FT RIGHT OF CENTERLINE, UP TO 102 FT AGL/747 FT MSL.

LINCOLNTON-LINCOLN COUNTY RGNL: NOTE: RWY 5, TREES BEGINNING 1913 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/999 FT MSL. NOTE: RWY 23, TREES BEGINNING 1395 FT FROM DER, 41 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/1059 FT MSL. TREES BEGINNING 2068 FT FROM DER, 480 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/1027 FT MSL.

LANCASTER COUNTY-MC WHIRTER FIELD: NOTE: RWY 6, TREES BEGINNING 176 FT FROM DER, 394 FT LEFT OF CENTERLINE, UP TO 26 FT AGL/526 FT MSL. VEHICLES ON ROADWAY 322 FT FROM DER, 401 FT RIGHT OF CENTERLINE, UP TO 15 FT AGL/517 FT MSL. TREES BEGINNING 4704 FT FROM DER, 1425 FT LEFT OF CENTERLINE, UP TO 80 FT AGL/630 FT MSL. NOTE: RWY 24, TREES BEGINNING 73 FT FROM DER, 492 FT LEFT OF CENTERLINE, UP TO 27 FT AGL/467 FT MSL.

STANLY COUNTY: NOTE: RWY 4R, TREE 4312 FT FROM DER, 374 FT RIGHT OF CENTERLINE, 78 FT AGL/692 FT MSL. TREE 1.2 NM FROM DER, 2063 FT LEFT OF CENTERLINE, 98 FT AGL/837 FT MSL. NOTE: RWY 22L, TREES BEGINNING 190 FT FROM DER, 142 FT RIGHT OF CENTERLINE UP TO 82 FT AGL/682 FT MSL. RAILROAD 438 FT FROM DER, 403 FT RIGHT OF CENTERLINE, 23 FT AGL/620 FT MSL.

ROWAN COUNTY: NOTE: RWY 2, TREES BEGINNING 106 FT FROM DER, 474 FT RIGHT OF CENTERLINE, UP TO 68 FT AGL/787 FT MSL. NOTE: RWY 20, TREES BEGINNING 167

QUALITY
15
CHECKED

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
 Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

FT FROM DER, 17 FT RIGHT OF CENTERLINE, UP TO 114 FT AGL/913 FT MSL. TREES BEGINNING 1323 FT FROM DER, 4 FT LEFT OF CENTERLINE, UP TO 97 FT AGL/896 FT MSL.
 BLDG 669 FT FROM DER, 361 FT LEFT OF CENTERLINE, 25 FT AGL/788 FT MSL.

CONTROLLING OBSTACLES:

CHARLOTTE/DOUGLAS INTL: RWY 5: 1634 FT MSL BLDG 351339.00N/0805032.00W. **RWY 36C:** 2749 FT MSL TOWER 352145.00N/0810918.00W. **RWY 36L:** 2755 FT MSL TOWER 352049.00N/0811014.00W.
CONCORD RGNL: RWY 2: 2349 FT MSL TOWER 353157.00N/0804746.00W. **RWY 20:** 1951 FT MSL TOWER 351715.00N/0804144.00W.
GASTONIA MUNI: RWY 3: 2755 FT MSL TOWER 352049.00N/0811014.00W. **RWY 21:** 2755 FT MSL TOWER 352049.00N/0811014.00W.
LINCOLNTON-LINCOLN COUNTY RGNL: RWY 5, 1759 FT MSL AAO 353355.99N/0810528.63W. **RWY 23,** 2720 FT MSL TOWER 352151.00N/0811112.00W.
STANLY COUNTY: RWY 4R: 639 FT MSL TREE 352434.97N/0800929.52W.
ROWAN COUNTY: RWY 20: 1125 FT MSL TOWER 353612.70N/0803254.42W, 1849 FT MSL TOWER 353533.00N/0803743.00W.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

CHART NOTE (CHARLOTTE/DOUGLAS INTL, LINCOLNTON-LINCOLN COUNTY RGNL, LANCASTER COUNTY-MC WHIRTER FIELD, STANLY COUNTY, ROWAN COUNTY ONLY):
 ACCELERATE TO 250 KIAS, IF UNABLE, ADVISE ATC. **CHART NOTE:** DO NOT EXCEED 280 KIAS UNTIL ADVISED BY ATC.

CHARLOTTE/DOUGLAS INTL - CHART: TOP ALTITUDE: 8000
CONCORD RGNL - CHART: TOP ALTITUDE: 3000
GASTONIA MUNI - CHART: TOP ALTITUDE: 3400
CHARLOTTE-MONROE EXECUTIVE - CHART : TOP ALTITUDE: 3000
ROCK HILL/YORK CO/BRYANT FIELD - CHART: TOP ALTITUDE: 3000
LINCOLNTON-LINCOLN COUNTY RGNL - CHART TOP ALTITUDE: 3000
ROWAN COUNTY - CHART TOP ALTITUDE: 3000
LANCASTER COUNTY-MC WHIRTER FIELD - CHART: TOP ALTITUDE: 3000
STANLY COUNTY - CHART: TOP ALTITUDE: 3000

AIRPORTS SERVED:

CHARLOTTE/DOUGLAS INTL
 CONCORD RGNL
 GASTONIA MUNI
 CHARLOTTE-MONROE EXECUTIVE
 ROCK HILL/YORK CO/BRYANT FIELD
 LINCOLNTON-LINCOLN COUNTY RGNL
 ROWAN COUNTY
 LANCASTER COUNTY-MC WHIRTER FIELD
 STANLY COUNTY

CHARLOTTE, NC
 CONCORD, NC
 GASTONIA, NC
 MONROE, NC
 ROCK HILL, SC
 LINCOLNTON, NC
 SALISBURY, NC
 LANCASTER, SC
 ALBEMARLE, NC

QUALITY
 15
 CHECKED

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

COMMUNICATIONS:

CHARLOTTE/DOUGLAS INTL: ATIS, CLEARANCE DELIVERY, GROUND, TOWER, DEP CON.
CONCORD RGNL: AWOS, CLEARANCE DELIVERY, GROUND, TOWER, CTAF, DEP CON.
GASTONIA MUNI, CHARLOTTE-MONROE EXECUTIVE, ROCK HILL/YORK CO/BRYANT FIELD: ASOS, CLEARANCE DELIVERY, CTAF, DEP CON.
LINCOLN-TON-LINCOLN COUNTY RGNL: ASOS, CLEARANCE DELIVERY, CTAF, DEP CON 134.75/257.2.
LANCASTER COUNTY-MC WHIRTER FIELD: ASOS, CLEARANCE DELIVERY, CTAF, DEP CON 120.05/307.8.
ROWAN COUNTY: ASOS, CLEARANCE DELIVERY, CTAF, DEP CON 128.325/307.8.
STANLY COUNTY: AWOS, CLEARANCE DELIVERY, GROUND, TOWER, CTAF, DEP CON 128.325/307.8.

FIXES AND/OR NAVAIDS:

AHN VORTAC, GQO VORTAC, VXV VORTAC, HRS VORTAC, SPA VORTAC, SUG VORTAC

REMARKS:**REQUIRED EFFECTIVE DATE:**

ROUTINE

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

CHANGES:

ADDED CHART: TOP ALTITUDES FOR:

CHARLOTTE/DOUGLAS INTL - CHART: TOP ALTITUDE: 8000
CONCORD RGNL - CHART: TOP ALTITUDE: 3000
GASTONIA MUNI - CHART: TOP ALTITUDE: 3400
CHARLOTTE-MONROE EXECUTIVE - CHART : TOP ALTITUDE: 3000
ROCK HILL/YORK CO/BRYANT FIELD - CHART: TOP ALTITUDE: 3000
LINCOLN-TON-LINCOLN COUNTY RGNL - CHART TOP ALTITUDE: 3000
ROWAN COUNTY - CHART TOP ALTITUDE: 3000
LANCASTER COUNTY-MC WHIRTER FIELD - CHART: TOP ALTITUDE: 3000
STANLY COUNTY - CHART: ALTITUDE: 3000

REASONS:

ATC REQUEST



DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

ARINC SUMMARY - 424-18 - SID

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ALL	CLT	010		IF		FB					
	DEBIE	CLT	010		IF		FB					
	DEBIE	DEBIE	020		TF		FB		255.0 ()	045.0		
	HARAY	CLT	010		IF		FB					
	HARAY	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	CLT	010		IF		FB					
	ZAVER	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	ZAVER	030		TF		FB		270.0 ()	025.0		

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CLT	N351125.04	W0805706.31	N3511.417	W08057.105
	DEBIE	N345549.06	W0814832.06	N3455.818	W08148.534
	HARAY	N350745.69	W0814541.18	N3507.762	W08145.686
	ZAVER	N350518.82	W0821600.72	N3505.314	W08216.012
	RW03	N351153.04	W0810910.33	N3511.884	W08109.172
	RW21	N351225.07	W0810849.29	N3512.418	W08108.822

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW03	00796	40
	RW21	00781	40

QUALITY
15
CHECKED

DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

ARINC SUMMARY - 424-18 - SID

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ALL	CLT	010		IF		FB					
	DEBIE	CLT	010		IF		FB					
	DEBIE	DEBIE	020		TF		FB		255.0 ()	045.0		
	HARAY	CLT	010		IF		FB					
	HARAY	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	CLT	010		IF		FB					
	ZAVER	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	ZAVER	030		TF		FB		270.0 ()	025.0		

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CLT	N351125.04	W0805706.31	N3511.417	W08057.105
	DEBIE	N345549.06	W0814832.06	N3455.818	W08148.534
	HARAY	N350745.69	W0814541.18	N3507.762	W08145.686
	ZAVER	N350518.82	W0821600.72	N3505.314	W08216.012
	RW06	N351232.23	W0805659.81	N3512.537	W08056.997
	RW18C	N351338.63	W0805711.41	N3513.644	W08057.190
	RW18L	N351329.04	W0805610.17	N3513.484	W08056.170
	RW18R	N351331.02	W0805802.71	N3513.517	W08058.045
	RW23	N351321.42	W0805552.12	N3513.357	W08055.869
	RW36C	N351159.97	W0805702.92	N3512.000	W08057.049
	RW36L	N351202.23	W0805755.07	N3512.037	W08057.918
	RW36R	N351203.45	W0805602.82	N3512.058	W08056.047

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW06	00706	51
	RW18C	00742	55
	RW18L	00746	56
	RW18R	00744	53
	RW23	00747	58
	RW36C	00692	57
	RW36L	00744	54
	RW36R	00724	58

QUALITY
15
CHECKED

DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

ARINC SUMMARY - 424-18 - SID

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ALL	CLT	010		IF		FB					
	DEBIE	CLT	010		IF		FB					
	DEBIE	DEBIE	020		TF		FB		255.0 ()	045.0		
	HARAY	CLT	010		IF		FB					
	HARAY	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	CLT	010		IF		FB					
	ZAVER	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	ZAVER	030		TF		FB		270.0 ()	025.0		

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CLT	N351125.04	W0805706.31	N3511.417	W08057.105
	DEBIE	N345549.06	W0814832.06	N3455.818	W08148.534
	HARAY	N350745.69	W0814541.18	N3507.762	W08145.686
	ZAVER	N350518.82	W0821600.72	N3505.314	W08216.012
	RW05	N350049.23	W0803737.01	N3500.821	W08037.617
	RW23	N350126.33	W0803648.65	N3501.439	W08036.811

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW05	00679	44
	RW23	00662	40

QUALITY
15
CHECKED

DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

ARINC SUMMARY - 424-18 - SID

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ALL	CLT	010		IF		FB					
	DEBIE	CLT	010		IF		FB					
	DEBIE	DEBIE	020		TF		FB		255.0 ()	045.0		
	HARAY	CLT	010		IF		FB					
	HARAY	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	CLT	010		IF		FB					
	ZAVER	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	ZAVER	030		TF		FB		270.0 ()	025.0		

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CLT	N351125.04	W0805706.31	N3511.417	W08057.105
	DEBIE	N345549.06	W0814832.06	N3455.818	W08148.534
	HARAY	N350745.69	W0814541.18	N3507.762	W08145.686
	ZAVER	N350518.82	W0821600.72	N3505.314	W08216.012
	RW06	N352841.46	W0811004.94	N3528.691	W08110.082
	RW23	N352917.07	W0810918.01	N3529.285	W08109.300

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW06	00877	58
	RW23	00867	40

DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

ARINC SUMMARY - 424-8A - SID

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ALL	CLT	010		IF		FB					
	DEBIE	CLT	010		IF		FB					
	DEBIE	DEBIE	020		TF		FB		255.0 ()	045.0		
	HARAY	CLT	010		IF		FB					
	HARAY	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	CLT	010		IF		FB					
	ZAVER	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	ZAVER	030		TF		FB		270.0 ()	025.0		

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CLT	N351125.04	W0805706.31	N3511.417	W08057.105
	DEBIE	N345549.06	W0814832.06	N3455.818	W08148.534
	HARAY	N350745.69	W0814541.18	N3507.762	W08145.686
	ZAVER	N350518.82	W0821600.72	N3505.314	W08216.012
	RW02	N352239.99	W0804241.00	N3522.667	W08042.683
	RW20	N352345.66	W0804226.19	N3523.761	W08042.437

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW02	00640	60
	RW20	00700	44

QUALITY
15
CHECKED

DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

ARINC SUMMARY - 424-18 - SID

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ALL	CLT	010		IF		FB					
	DEBIE	CLT	010		IF		FB					
	DEBIE	DEBIE	020		TF		FB		255.0 ()	045.0		
	HARAY	CLT	010		IF		FB					
	HARAY	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	CLT	010		IF		FB					
	ZAVER	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	ZAVER	030		TF		FB		270.0 ()	025.0		

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CLT	N351125.04	W0805706.31	N3511.417	W08057.105
	DEBIE	N345549.06	W0814832.06	N3455.818	W08148.534
	HARAY	N350745.69	W0814541.18	N3507.762	W08145.686
	ZAVER	N350518.82	W0821600.72	N3505.314	W08216.012
	RW06	N344307.49	W0805146.12	N3443.125	W08051.769
	RW24	N344337.96	W0805045.86	N3443.633	W08050.764

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW06	00460	47
	RW24	00486	43



DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

ARINC SUMMARY - 424-18 - SID

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ALL	CLT	010		IF		FB					
	DEBIE	CLT	010		IF		FB					
	DEBIE	DEBIE	020		TF		FB		255.0 ()	045.0		
	HARAY	CLT	010		IF		FB					
	HARAY	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	CLT	010		IF		FB					
	ZAVER	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	ZAVER	030		TF		FB		270.0 ()	025.0		

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CLT	N351125.04	W0805706.31	N3511.417	W08057.105
	DEBIE	N345549.06	W0814832.06	N3455.818	W08148.534
	HARAY	N350745.69	W0814541.18	N3507.762	W08145.686
	ZAVER	N350518.82	W0821600.72	N3505.314	W08216.012
	RW02	N353819.03	W0803122.23	N3538.317	W08031.371
	RW20	N353911.33	W0803103.87	N3539.189	W08031.065

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW02	00769	55
	RW20	00766	46

DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 201	25 JUNE 2015

ARINC SUMMARY - 424-18 - SID

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ALL	CLT	010		IF		FB					
	DEBIE	CLT	010		IF		FB					
	DEBIE	DEBIE	020		TF		FB		255.0 ()	045.0		
	HARAY	CLT	010		IF		FB					
	HARAY	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	CLT	010		IF		FB					
	ZAVER	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	ZAVER	030		TF		FB		270.0 ()	025.0		

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CLT	N351125.04	W0805706.31	N3511.417	W08057.105
	DEBIE	N345549.06	W0814832.06	N3455.818	W08148.534
	HARAY	N350745.69	W0814541.18	N3507.762	W08145.686
	ZAVER	N350518.82	W0821600.72	N3505.314	W08216.012
	RW02	N345849.49	W0810332.27	N3458.825	W08103.538
	RW20	N345942.85	W0810319.40	N3459.714	W08103.323

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW02	00666	41
	RW20	00661	40

QUALITY
15
CHECKED

DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BOBCAT	SIX	BOB6.BOB	FIVE	15 DEC 2011	25 JUNE 2015

ARINC SUMMARY - 424-18 - SID

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	RW04R	CLT	010		IF		FB					
	RW22L	CLT	010		IF		FB					
	DEBIE	CLT	010		IF		FB					
	DEBIE	DEBIE	020		TF		FB		255.0 ()	045.0		
	HARAY	CLT	010		IF		FB					
	HARAY	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	CLT	010		IF		FB					
	ZAVER	HARAY	020		TF		FB		270.0 ()	040.0		
	ZAVER	ZAVER	030		TF		FB		270.0 ()	025.0		

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CLT	N351125.04	W0805706.31	N3511.417	W08057.105
	DEBIE	N345549.06	W0814832.06	N3455.818	W08148.534
	HARAY	N350745.69	W0814541.18	N3507.762	W08145.686
	ZAVER	N350518.82	W0821600.72	N3505.314	W08216.012
	RW04R	N352433.51	W0800923.36	N3524.559	W08009.389
	RW22L	N352516.85	W0800843.20	N3525.281	W08008.720

RUNWAY DATA	THRESHOLD ELEVATION	TCH
RWY		
RW04R	00609	39
RW22L	00577	40

QUALITY
15
CHECKED