

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
JEPAX (IF/IAF)	JIBMI (FB)	058.68 / 6.20	2200	LP: RW06 LNAV: RW06
JIBMI (FAF)	XEJLI/2.50 NM TO RW06 (FB)	058.74 / 2.98		
XEJLI/2.50 NM TO RW06	RW06 (MAP) (FO)	058.77 / 2.50		CLIMBING RIGHT TURN TO 3000 DIRECT JEPAX AND HOLD.
RW06 (MAP)	828 MSL	058.77		
828 MSL	JEPAX (FO)		3000	ADDITIONAL FLIGHT DATA: CHART FAS OBST: 709 TREES 371155N/0871159W CHART FAS OBST: 793 TOWER 371145N/0871238W WAAS CHANNEL # 56527 REFERENCE PATH ID: W06A JIBMI TO RW06: 3.00/40. LTP HAE: 96.2 M

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD SW JEPAX, RT, 058.68 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 058.74 FAF: JIBMI DIST FAF TO MAP: 5.48 THLD: 5.48
- MIN. ALT: JEPAX 3000, JIBMI 2200, XEJLI/2.50 NM TO RW06 1240
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCTP: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 3W

EPOCH YEAR: 2010

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X						
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	960	1	545	960	1	545	960	1 5/8	545	960	1 5/8	545			
LNAV MDA	1100	1	685	1100	1	685	1100	2	685	1100	2	685			
CIRCLING	1100	1	672	1100	1	672	1100	2	672	1100	2 1/4	672			

NOTES:

CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 6 PROCEDURE NA AT NIGHT.
CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 24 NA AT NIGHT.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
(SEE FORM 8260-10)

CITY AND STATE GREENVILLE, KY	ELEVATION: 428 THRE: 415 AIRPORT NAME: MUHLENBERG COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 6, ORIG 31 MAY 2012	SUP: AMDT: NONE DATED
----------------------------------	----------------------------------------------------------------	------------------------------	---------------------------------------------------------------------------------	-----------------------------

QUALITY
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OWENSBORO ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET. INCREASE LP CATS C/D VISIBILITY 1/8 MILE, LNAV CAT B AND CIRCLING CATS B/D VISIBILITY 1/4 MILE, AND LNAV CATS C/D AND CIRCLING CAT C VISIBILITY 1/2 MILE.

TAA

	FROM	TO	ALT
1.	329/30 CW 149/30 (NOPT)	JEPAX (IF/IAF) (FB)	3000
2.	149/30 CW 329/30	JEPAX (IF/IAF) (FO)	3000

QUALITY
CHECKED

CITY AND STATE
GREENVILLE, KY

ELEVATION: 428 THRE: 415
AIRPORT NAME:
MUHLENBERG COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 6, ORIG
31 MAY 2012

SUP:
AMDT: NONE
DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER M21
RUNWAY RW06
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W06A
LTP/FTP LATITUDE 371320.5490N
LTP/FTP LONGITUDE 0870948.5680W
LTP/FTP ELLIPSOIDAL HEIGHT +00962
FPAP LATITUDE 371410.6800N
FPAP LONGITUDE 0870816.2900W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1224
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 0.0

CRC REMAINDER

28C8A9F6

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K5
LTP ORTHOMETRIC HEIGHT +01264
FPAP ORTHOMETRIC HEIGHT +01264

QUALITY
6
CHECKED

CITY AND STATE

GREENVILLE, KY

ELEVATION: 428

THRE: 415

AIRPORT NAME:

MUHLENBERG COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 6, ORIG

31 MAY 2012

SUP:

AMDT:

NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP M21 K5FR06	AJEPAX	010JEPAXK5EA0EE	AR	HF		05870040	+	03000	18000			A	JS
SUSAP M21 K5FR06	R	010JEPAXK5EA0E	I	IF			+	03000	18000			A	JS
SUSAP M21 K5FR06	R	020JIBMIK5EA1E	F	051TF		05870062	+	02200				A	JS
SUSAP M21 K5FR06	R	020JIBMIK5EA2WALP			N	ALNAV							JS
SUSAP M21 K5FR06	R	021XEJLIK5EA0E	S	031TF		05870030	V	0124001251		-300		A	JS
SUSAP M21 K5FR06	R	030RW06 K5PGOGY	M	031TF		05880025		00455		-300		A	JS
SUSAP M21 K5FR06	R	040	0	M	CA	0588	+	00828				A	JS
SUSAP M21 K5FR06	R	050JEPAXK5EA0EY	R	DF			+	03000				A	JS
SUSAP M21 K5FR06	R	060JEPAXK5EA0EE	R	HM		05870040	+	03000				A	JS

[illegible][illegible]

QUALITY
COUNCIL

SUP:	
AMDT:	NONE
DATED:	