

<b>RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
<b>TERMINAL ROUTES</b>				<b>MISSED APPROACH</b>											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW18  CLIMB TO 440 THEN CLIMBING LEFT TURN TO 2000 DIRECT SOLON AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD S, LT, 354.00 INBOUND. CHART FAS OBST: 423 TOWER 274900N/0973031W DISTANCE TO THLD FROM 200 HATH: 0.47 NM. CHART VDP AT 1.78 MILES TO RW18* *LNAV ONLY. WAAS CHANNEL # 53635 REFERENCE PATH ID: W18A CHART CIRCLING ICON LTP HAE: -14.5 M											
WORRY (IAF)	CAVLA (FB)	232.05 / 15.66	2100												
ATHIS (IAF)	CAVLA (FB)	105.71 / 19.15	2100												
CAVLA (IF)	PEERS (FB)	175.11 / 5.95	1700												
PEERS (FAF)	RW18 (MAP) (FO)	175.11 / 5.05													
RW18 (MAP)	440 MSL	175.11													
440 MSL	SOLON (FO)		2000												
1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF) 2. PROFILE STARTS AT CAVLA 3. FAC: 175.11 FAF: PEERS DIST FAF TO MAP: 5.05 THLD: 5.05 4. MIN. ALT: CAVLA 2100, PEERS 1700 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: 1700 GS ALT AT: PEERS 1700 OM: MM: IM: 7. GS ANGLE: 3.00 TCH: 52.0 34:1 IS CLEAR 8. MSA FROM: RW18 2200				MAG VAR: 4E EPOCH YEAR: 2015											
<b>MINIMUMS</b>															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @									
CATEGORY =====>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	240	1/2	200	240	1/2	200	240	1/2	200	240	1/2	200	240	1/2	200
LNAV/VNAV DA	343	1/2	303	343	1/2	303	343	1/2	303	343	1/2	303	343	1/2	303
LNAV MDA	660	1/2	620	660	1/2	620	660	1 3/8	620	660	1 3/8	620	660	1 3/8	620
CIRCLING	660	1	614	660	1	614	820	2 1/4	774	820	2 1/2	774	820	2 3/4	774
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -1C (31F) OR ABOVE 54C (130F). CHART NOTE: FOR INOPERATIVE MALSR, INCREASE LPV CAT E VISIBILITY TO 3/4 MILE; LNAV/VNAV CAT E VISIBILITY TO 1 MILE; LNAV CAT E VISIBILITY TO 1 7/8 MILE. CHART NOTE: DME/DME RNP-0.3 NA. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 46 THRE: 40		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:		SUP: RNAV (GPS) RWY 17							
CORPUS CHRISTI, TX		AIRPORT NAME: CORPUS CHRISTI INTL				RNAV (GPS) RWY 18, AMDT 1 6 FEBRUARY 2014		AMDT: ORIG							
								DATED 07/10/2003							

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT ATHIS ON V568 WESTBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT WORRY ON V13-407 NORTHEAST BOUND.

QUALITY  
3 A  
CHECKED

CITY AND STATE

CORPUS CHRISTI, TX

ELEVATION: 46

THRE: 40

AIRPORT NAME:

CORPUS CHRISTI INTL

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, AMDT 1

6 FEBRUARY 2014

SUP: RNAV (GPS) RWY 17

AMDT: ORIG

DATED: 07/10/2003

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCRP
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	274652.6715N
LTP/FTP LONGITUDE	0972946.8675W
LTP/FTP ELLIPSOIDAL HEIGHT	-00145
FPAP LATITUDE	274523.3380N
FPAP LONGITUDE	0972945.3075W
THRESHOLD CROSSING HEIGHT (TCH)	00052.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0712
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER 4F15C411

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00120
FPAP ORTHOMETRIC HEIGHT	+00120

CITY AND STATE  
CORPUS CHRISTI, TX

ELEVATION: 46 THRE: 40  
AIRPORT NAME:  
CORPUS CHRISTI INTL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 18, AMDT 1  
6 FEBRUARY 2014

SUP: RNAV (GPS) RWY 17  
AMDT: ORIG  
DATED: 07/10/2003

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible][illegible]

SUP:	RNAV (GPS) RWY 17
AMDT:	ORIG
DATED:	07/10/2003

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ATHIS	ATHIS	010	IAF	IF		FB					
	ATHIS	CAVLA	020		TF		FB	1.0	105.7(109.7T)	019.2	AA 02100	
	WORRY	WORRY	010	IAF	IF		FB					
	WORRY	CAVLA	020		TF		FB	1.0	232.1(236.1T)	015.7	AA 02100	
		CAVLA	010	FACF	IF		FB				AA 02100	
		PEERS	020	FAF	TF		FB	0.5	175.1(179.1T)	006.0	AA 01700	
		RW18	030	MAP	TF		FO	0.3	175.1(179.1T)	005.1	AT 00092	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		175.1(179.1T)		AA 00440	
	SOLO	050		DF	L	FO				AA 02000	
	SOLO	060		HM	L	FO		354.0(358.0T)	004.0	AA 02000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ATHIS	N280424.46	W0975019.74	N2804.408	W09750.329
	CAVLA	N275754.39	W0972958.45	N2757.907	W09729.974
	PEERS	N275156.53	W0972952.18	N2751.942	W09729.870
	SOLO	N272609.77	W0972541.57	N2726.163	W09725.693
	WORRY	N280641.17	W0971518.36	N2806.686	W09715.306
	RW18	N274652.67	W0972946.87	N2746.878	W09729.781

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW18	00040	52

CITY AND STATE  
CORPUS CHRISTI, TX

ELEVATION: 46      THRE: 40  
 AIRPORT NAME:  
 CORPUS CHRISTI INTL

FACILITY  
IDENTIFIER:  
 RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:  
 RNAV (GPS) RWY 18, AMDT 1  
 6 FEBRUARY 2014

SUP: RNAV (GPS) RWY 17  
 AMDT: ORIG  
 DATED: 07/10/2003