

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
LATON (IAF)	VIS VOR/DME (FB)	084.09 / 3.39	2000	LNAV: RW13 CLIMBING RIGHT TURN TO 2000 DIRECT VIS VOR/DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 287.70 INBOUND. CHART FAS OBST: 555 TOWER 361202N/1192304W CHART FOOTHILL 2 MOA. CHART PORTERVILLE MOA. CHART LEMOORE A-E MOA'S. NIRFY TO RW13: 3.04/40.
DINUB (IAF)	VIS VOR/DME (FB)	231.10 / 8.49	2000	
VIS VOR/DME (IF)	NIRFY (FB)	135.42 / 9.15	2000	

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT VIS VOR/DME
3. FAC: 131.93 FAF: NIRFY DIST FAF TO MAP: 5.25 THLD: 5.25
4. MIN. ALT: VIS VOR/DME 2000, NIRFY 2000
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR
8. MSA FROM: RW13 8700

MAG VAR: 15E EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:	<input type="checkbox"/>	STANDARD	<input checked="" type="checkbox"/>	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	<input checked="" type="checkbox"/>											
CATEGORY	=====	A			B			C			D			E			
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA		800	1	535	800	1	535	800	1 1/2	535		NA					
CIRCLING		840	1	575	840	1	575	840	1 1/2	575		NA					

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VISALIA ALTIMETER SETTING AND INCREASE
SEE 8260-10

QUALITY
5
CHECKED

CITY AND STATE TULARE, CA	ELEVATION: 265 TDZE: 265 AIRPORT NAME: MEFFORD FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMD'T NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG 29 JUL 2010	SUP: AMD'T: NONE DATED
----------------------------------	--	---------------------------------	---	------------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

ALL MDA 40 FEET AND INCREASE CIRCLING CAT C VISIBILITY 1/4 MILE.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT LATON VIA V23 NORTHWEST BOUND.

QUALITY
CHECKED

CITY AND STATE

TULARE, CA

ELEVATION: 265 TDZE: 265

AIRPORT NAME:

MEFFORD FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 13, ORIG

29 JUL 2010

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
4
CHECKED

CITY AND STATE TULARE, CA	ELEVATION: 265 TDZE: 265 AIRPORT NAME: MEFFORD FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG 29 JUL 2010	SUP:
				AMDT: NONE
				DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	NONE
DATED:	

PAGE 4 OF 4 PAGES