

PAGE 1 OF 2 PAGES

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: RWY 15 STRAIGHT-IN AND CIRCLING MINIMUMS NA AT NIGHT.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

*1660 WHEN USING ST JAMES ALTIMETER SETTING.

CITY AND STATE

NEW ULM, MN

ELEVATION: 1011

THRE: 1005

AIRPORT NAME:

NEW ULM MUNI

FACILITY
IDENTIFIER:

ULM

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

NDB RWY 15, AMDT 2

2 MAY 2013

SUP: NDB OR GPS RWY
15

AMDT: 1

DATED: 07/10/2003