

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: DVL VOR/DME						
										CLIMB TO 3100 THEN LEFT TURN DIRECT DVL VOR/DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 141.00 INBOUND. CHART FAS OBST: 1688 ELEV 480815N/0985440W CHART VDP AT 1.94 DME; DISTANCE VDP TO THLD 1.34 MILES. CHART CIRCLING ICON. ZUDUB TO RW13: 2.92/45. FAC CROSSES RWY C/L EXTENDED 3006 FROM THLD.						
1. PT <u>L</u> SIDE OF COURSE <u>318.45</u> OUTBOUND <u>3100</u> FT WITHIN <u>10</u> MILES OF <u>DVL VOR/DME</u> (IAF) 2. _____ 3. FAC <u>138.45</u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT <u>ZUDUB/2.50 DME 2100*</u> 8. MSA FROM: <u>DVL VOR/DME 3400</u>										MAG VAR: 7E		EPOCH YEAR: 2000				
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @						
CATEGORY >>>>>		A		B		C		D		E		F		G		
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-13		2100	1	630	2100	1	630	2100	1 3/4	630	2100	1 3/4	630			
CIRCLING		2100	1	644	2100	1	644	2240	2 1/4	784	2240	2 1/2	784			
ZUDUB FIX MINIMUMS (DME REQUIRED)																
S-13		1940	1	470	1940	1	470	1940	1 3/8	470	1940	1 3/8	470			
CIRCLING		2000	1	544	2000	1	544	2240	2 1/4	784	2240	2 1/2	784			
NOTES: CHART NOTE: VDP NA WITH CANDO ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CANDO ALTIMETER SETTING AND INCREASE ALL MDA 80 FT, AND INCREASE S-13 AND CIRCLING CATS C AND D VISIBILITY 1/4 MILE, INCREASE ZUDUB FIX MINIMUMS S-13 AND CIRCLING CATS C AND D VISIBILITY 1/4 MILE. CHART PROFILE NOTE: *2180 WHEN USING CANDO ALTIMETER SETTING.																
CITY AND STATE DEVILS LAKE, ND				ELEVATION: 1456 THRE: 1470 AIRPORT NAME: DEVILS LAKE RGNL				FACILITY IDENTIFIER: DVL		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 13, AMDT 1 12 DECEMBER 2013				SUP AMDT ORIG-B DATE 08/26/2010		

QUALITY
2
CHECKED