

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		TERMINAL ROUTES				MISSED APPROACH									
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW22 CLIMB TO 2700 DIRECT XIHAM AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 043.95 INBOUND. CHART FAS OBST: 349 TREE 360755N/0905453W DISTANCE TO THLD FROM 250 HATH: 0.64 NM. CHART VDP AT 0.89 MILES TO RW22* *LNAV ONLY. WAAS CHANNEL # 82125 REFERENCE PATH ID: W22A LTP HAE: 55 M											
ESEGE (IF/IAF)	OYFAL (FB)	224.15 / 6.80	1900												
OYFAL (FAF)	JOMOS/1.60 NM TO RW22 (FB)	224.09 / 3.37													
JOMOS/1.60 NM TO RW22	RW22 (MAP) (FO)	224.07 / 1.60													
RW22 (MAP)	523 MSL	224.07													
523 MSL	XIHAM (FO)		2700												
1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF) 2. HOLD NE ESEGE, RT, 224.15 INBOUND, 2700 FT. IN LIEU OF PT (IAF) 3. FAC: 224.09 FAF: OYFAL DIST FAF TO MAP: 4.97 THLD: 4.97 4. MIN. ALT: ESEGE 2700, OYFAL 1900, JOMOS/1.60 NM TO RW22 820* 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: 1900 GS ALT AT: OYFAL 1900 OM: MM: IM: 7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS CLEAR 8. MSA FROM:				MAG VAR: 1E EPOCH YEAR: 2000											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @									
CATEGORY =====>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	523	1	250	523	1	250	523	1	250	523	1	250			
LNAV/VNAV DA	523	1	250	523	1	250	523	1	250	523	1	250			
LNAV MDA	600	1	327	600	1	327	600	1	327	600	1	327			
CIRCLING	760	1	481	760	1	481	760	1 1/2	481	840	2	561			
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING JONESBORO ALTIMETER SETTING. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 42C (107F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VDP NA WITH JONESBORO ALTIMETER SETTING. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 279 THRE: 273		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
WALNUT RIDGE, AR		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 22, AMDT 1				AMDT: ORIG-B					
		WALNUT RIDGE RGNL				20 OCT 2011				DATED 03/28/2008					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JONESBORO ALTIMETER SETTING AND INCREASE ALL DA 54 FEET AND ALL MDA 60 FEET; INCREASE LPV ALL CATS VISIBILITY 1/4 MILE, LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE AND LNAV CAT C AND D VISIBILITY 1/8 MILE.

TAA

	FROM	TO	ALT
1.	134/30 CW 314/30 (NOPT)	ESEGE (IAF) (FB)	2700
2.	314/30 CW 134/30	ESEGE (IAF) (FO)	3100

CITY AND STATE
WALNUT RIDGE, AR

ELEVATION: 279 THRE: 273
AIRPORT NAME:
WALNUT RIDGE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 22, AMDT 1
20 OCT 2011

SUP:
AMDT: ORIG-B
DATED: 08/28/2008

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KARG
RUNWAY	RW22
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W22A
LTP/FTP LATITUDE	360730.7545N
LTP/FTP LONGITUDE	0905509.4265W
LTP/FTP ELLIPSOIDAL HEIGHT	+00550
FPAP LATITUDE	360627.7000N
FPAP LONGITUDE	0905627.2500W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0920
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

9A7E5796

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00832
FPAP ORTHOMETRIC HEIGHT	+00832

CITY AND STATE
WALNUT RIDGE, AR

ELEVATION: 279 THRE: 273
AIRPORT NAME:
WALNUT RIDGE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 22, AMDT 1
20 OCT 2011

SUP:
AMDT: ORIG-B
DATED: 08/28/2008

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KARGK4FR22	AESEGE	010E	SEGEK4EA0EE	AR	HF		22420040	+	02700	18000		A	JS
SUSAP KARGK4FR22	R	010E	SEGEK4EA0E	I	IF			+	02700	18000		A	JS
SUSAP KARGK4FR22	R	020OYFALK4EA1E	F	051TF			22420068	+	01900			A	JS
SUSAP KARGK4FR22	R	020OYFALK4EA2WALPV			ALNAV/VNAV	ALNAV							JS
SUSAP KARGK4FR22	R	021JOMOSK4EA0E	S	031TF			22410034	V	0082000827		-300	A	JS
SUSAP KARGK4FR22	R	030RW22 K4PG0GY	M	031TF			22410016		00318		-300	A	JS
SUSAP KARGK4FR22	R	040	0	M	CA		2241	+	00523			A	JS
SUSAP KARGK4FR22	R	050XIHAMK4EA0EY		DF				+	02700			A	JS
SUSAP KARGK4FR22	R	060XIHAMK4EA0EE	R	HM			04400040	+	02700			A	JS

[illegible][illegible]

SUP:	
AMDT:	ORIG-B
DATED:	08/28/2008