

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 2.82 MILES AFTER VOF NDB
CANUK INT	VOF NDB	005.98 / 24.76	2500	CLIMB TO 2000 THEN CLIMBING LEFT TURN TO 2500 DIRECT VOF NDB AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD E, LT, 275.15 INBOUND. CHART FAS OBST: 999 TREE 333905N/0835008W VOF NDB TO RW28: 3.49/45.

1. PT R SIDE OF COURSE 095.15 OUTBOUND 2500 FT WITHIN 10 MILES OF VOF NDB (IAF)
2. _____
3. FAC 275.15 FAF VOF NDB DIST FAF TO MAP 2.82 THLD 2.82
4. MIN. ALT VOF NDB 1900
8. MSA FROM: VOF NDB 3600

MAG VAR: 3W

EPOCH YEAR:1990

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X							
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-28	1300	1	491	1300	1	491	1300	1 3/8	491	1300	1 3/8	491				
CIRCLING	1300	1	491	1360	1	551	1360	1 1/2	551	1360	2	551				

NOTES:

CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 10 NA AT NIGHT.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LAWRENCEVILLE ALTIMETER SETTING AND (SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE ATLANTA, GA	ELEVATION: 809 THRE: 809 AIRPORT NAME: COVINGTON MUNI	FACILITY IDENTIFIER: VOF	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 28, AMDT 3 15 NOVEMBER 2012	SUP
				AMDT 2
				DATE 11/20/2008



**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

INCREASE ALL MDA 100 FT AND S-28 CATS C/D VISIBILITIES 3/8 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE.



CITY AND STATE
ATLANTA, GA

ELEVATION: 809 THRE: 809
AIRPORT NAME:
COVINGTON MUNI

FACILITY
IDENTIFIER:
VOF

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
NDB RWY 28, AMDT 3
15 NOVEMBER 2012

SUP:
AMDT: 2
DATED: 11/20/2008