U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
ACO VOR/DME	AKRON LOM	258.89 / 8.74	3100

MISSED APPROACH

MAP: 4.76 MILES AFTER AKRON LOM

CLIMBING LEFT TURN TO 3100 DIRECT AKRON LOM AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD S, RT, 351.10 INBOUND.
FAS OBST: 1419 AAO 410457N/0812443W
AK LOM TO RW01: 3.25/42
CHART AKRON FULTON INTL ASOS.

1. PT **L** SIDE OF COURSE **171.10** OUTBOUND **3100** FT WITHIN **10** MILES OF **AKRON LOM** (IAF)
2.
3. FAC **351.10** FAF **AKRON LOM** DIST FAF TO MAP **4.76** THLD **4.76**
4. MIN. ALT **AKRON LOM 2800**
8. MSA FROM: **AK LOM 3100**

MAG VAR: **7W** EPOCH YEAR: **1990**

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A **X**

CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-1	1760	1	643	1760	1	643	1760	1 7/8	643		NA				
CIRCLING	1760	1	626	1760	1	626	1760	1 7/8	626		NA				

NOTES:

CHART NOTE: USE AKRON FULTON INTL ALTIMETER SETTING; WHEN NOT RECEIVED, USE AKRON-CANTON RGNL ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET.
CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 01 PROCEDURE NA AT NIGHT.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

CITY AND STATE	ELEVATION: 1134 THRE: 1117	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP
KENT, OH	AIRPORT NAME: KENT STATE UNIV	AK	NDB RWY 1, AMDT 13 PŸ &%" 201T	AMDT 12
				DATE 11/25/2004