

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW31
SUXPU (IF/IAF)	PUYCO (FB)	314.48 / 6.02	2800	CLIMB TO 3000 DIRECT CUHSU AND HOLD.
PUYCO (FAF)	JOLMU/2.50 NM TO RW31 (FB)	314.41 / 2.69		
JOLMU/2.50 NM TO RW31	RW31 (MAP) (FO)	314.38 / 2.50		
RW31 (MAP)	1574 MSL	314.38		
1574 MSL	CUHSU (FO)		3000	ADDITIONAL FLIGHT DATA: HOLD NW, RT, 134.21 INBOUND. CHART FAS OBST: 1349 TREE 401259N/0805936W CHART KHLG AWOS-3 PUYCO TO RW31: 3.00/40

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD SE SUXPU, RT, 314.48 INBOUND, 3100 FT. IN LIEU OF PT (IAF)
3. FAC: 314.41 FAF: PUYCO DIST FAF TO MAP: 5.19 THLD: 5.19
4. MIN. ALT: SUXPU 3100, PUYCO 2800, JOLMU/2.50 NM TO RW31 1940
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR
8. MSA FROM:

MAG VAR: 8W

EPOCH YEAR: 2000

MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X							
CATEGORY ==>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	1660	1	552	1660	1	552		NA			NA					
CIRCLING	1780	1	606	1820	1	646		NA			NA					

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PROFILE NOTE: VGS1 AND DESCENT ANGLES NOT COINCIDENT.
CHART NOTE: USE WHEELING ALTIMETER SETTING; WHEN NOT RECEIVED, USE WASHINGTON ALTIMETER SETTING
(SEE FORM 8260-10)

CITY AND STATE CADIZ, OH	ELEVATION: 1174 THRE: 1108 AIRPORT NAME: HARRISON COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 31, ORIG 05 MAY 2011	SUP:
				AMDT: NONE
				DATED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

AND INCREASE ALL MDA 40 FEET.

CHART NOTE: WHEN VGSI INOP, PROCEDURE NA AT NIGHT.

TAA

	FROM	TO	ALT
1.	224/30 CW 044/30 (NOPT)	SUXPU (IF/IAF) (FB)	3100
2.	044/30 CW 224/30	SUXPU (IAF) (FO)	3400

CITY AND STATE
CADIZ, OH

ELEVATION: 1174 THRE: 1108
AIRPORT NAME:
HARRISON COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 31, ORIG
05 MAY 2011

SUP:
AMDT: NONE
DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

CITY AND STATE CADIZ, OH	ELEVATION: 1174 THRE: 1108 AIRPORT NAME: HARRISON COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 31, ORIG 05 MAY 2011	SUP:
				AMDT: NONE
				DATED: