

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW05R CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 3000 DIRECT XUB VOR AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, LT, 176.00 INBOUND. CHART FAS OBST: 830 APRON LIGHT 394828N/0825656W 980 AAO 394455N/0830244W DISTANCE TO THLD FROM 200 HATH: 0.46 NM. CHART VDP AT 1.00 MILES TO RW05R* *LNAV ONLY. WAAS CHANNEL # 78410 REFERENCE PATH ID: W05A LTP HAE: 189.9 M							
TARTO		OYOVU (FB)		276.48 / 17.80			3000									
OYOVU (IAF)		YERKU (NOPT) (FB)		320.38 / 8.72			3000									
GAILL (IAF)		YERKU (NOPT) (FB)		080.58 / 13.11			3000									
YERKU (IF/IAF)		FOGEB (FB)		050.17 / 7.89			2500									
FOGEB (FAF)		YABUC/1.60 NM TO RW05R (FB)		050.25 / 3.77												
YABUC/1.60 NM TO RW05R (SEE FORM 8260-10)		RW05R (MAP) (FO)		050.28 / 1.60												
1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)										MAG VAR: 5W EPOCH YEAR: 1985						
2. HOLD SW YERKU, RT, 050.17 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																
3. FAC: 050.25 FAF: FOGEB DIST FAF TO MAP: 5.37 THLD: 5.37																
4. MIN. ALT: YERKU 3000, FOGEB 2500, YABUC/1.60 NM TO RW05R 1220*																
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:																
6. MIN GS INCPT: 2500 GS ALT AT: FOGEB 2500 OM: MM: IM:																
7. GS ANGLE: 3.00 TCH: 53.9 34:1 IS CLEAR																
8. MSA FROM: RW05R 3100																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @							
CATEGORY ==>		A			B			C			D			E		
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA		935	2400	200	935	2400	200	935	2400	200	935	2400	200			
LNAV/VNAV DA		1011	2400	276	1011	2400	276	1011	2400	276	1011	2400	276			
LNAV MDA		1120	2400	385	1120	2400	385	1120	3500	385	1120	3500	385			
CIRCLING		1180	1	436	1200	1	456	1200	1 1/2	456	1300	2	556			
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING PORT COLUMBUS INTL ALTIMETER SETTING. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 39C (102F). CHART NOTE: CIRCLING NA NW OF RWY 5L-23R. CHART NOTE: DME/DME RNP-0.3 NA. (SEE FORM 8260-10)																
CITY AND STATE COLUMBUS, OH		ELEVATION: 744 THRE: 735 AIRPORT NAME: RICKENBACKER INTL			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 5R, AMDT 1 25 AUG 2011					SUP: AMDT: ORIG DATED 01/15/2009				