

<b>US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION</b>		<b>RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33</b>		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW12  CLIMB TO 4100 DIRECT DIYER AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD SE, RT, 304.61 INBOUND. CHART FAS OBST: 1726 TANK 295900N/0990526W CHART: 1916 TREE 300021N/0990820W DISTANCE TO THLD FROM 250 HATH: 0.66 NM. WAAS CHANNEL # 45628 REFERENCE PATH ID: W12A LTP HAE: 457.9 M									
OBUCO (IF/IAF)		LAVIC (FB)		124.44 / 7.00				3300											
LAVIC (FAF)		HALOL/2.80 NM TO RW12 (FB)		124.49 / 2.49															
HALOL/2.80 NM TO RW12		RW12 (MAP) (FO)		124.51 / 2.80															
RW12 (MAP)		1826 MSL		124.51															
1826 MSL		DIYER (FO)						4100											
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. HOLD NW OBUCO, RT, 124.44 INBOUND, 4000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>124.49</u> FAF: <u>LAVIC</u> DIST FAF TO MAP: <u>5.29</u> THLD: <u>5.29</u> 4. MIN. ALT: OBUCO 4000, LAVIC 3300, HALOL/2.80 NM TO RW12 2500* 5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u> 6. MIN GS INCPT: <u>3300</u> GS ALT AT: <u>LAVIC 3300</u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>40.0</u> 34:1 IS NOT CLEAR 8. MSA FROM: <u>      </u>																MAG VAR: 6E		EPOCH YEAR: 2005	
<b>MINIMUMS</b>																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	1826	1	250	1826	1	250	1826	1	250	1826	1	250							
LNAV/VNAV DA	1926	1 1/8	350	1926	1 1/8	350	1926	1 1/8	350	1926	1 1/8	350							
LNAV MDA	1980	1	404	1980	1	404	1980	1 1/8	404	1980	1 1/8	404							
CIRCLING																			
	2320	1	703	2340	1	723	2380	2 1/4	763	2380	2 1/2	763							
NOTES:																			
CHART NOTE: BARO-VNAV NA WHEN USING GILLESPIE COUNTY ALTIMETER SETTING.										@ CAT C 800-2 1/4, CAT D 800-2 1/2									
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C (0F) OR ABOVE 34C (93F).										@ NA WHEN LOCAL WEATHER NOT AVAILABLE.									
CHART NOTE: DME/DME RNP-0.3 NA.																			
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.																			
(SEE FORM 8260-10)																			
CITY AND STATE		ELEVATION: 1617 THRE: 1576		AIRPORT NAME:		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:							
KERRVILLE, TX				KERRVILLE MUNI/LOUIS SCHREINER FIELD		RNAV		RNAV (GPS) RWY 12, AMDT 1 5 APR 2012				AMDT: ORIG							
												DATED 10/27/2005							

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGS1 AND RNAV GLIDEPATH NOT COINCIDENT.

\*LNAV ONLY


CHART NOTE: WHEN VGS1 INOP, PROCEDURE NA AT NIGHT.

CHART NOTE: WHEN VGS1 INOP, CIRCLING RWY 3/21 NA AT NIGHT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GILLESPIE COUNTY ALTIMETER SETTING AND INCREASE ALL DA 54 FEET, AND ALL MDA 60 FEET, INCREASE LNAV/VNAV ALL CATS, LNAV AND CIRCLING CAT C/D VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	034/30 CW 214/30 (NOPT)	OBUCO (IF/IAF) (FB)	4000
2.	214/30 CW 034/30	OBUCO (IF/IAF) (FO)	4100



CITY AND STATE  
KERRVILLE, TX

ELEVATION: 1617      THRE: 1576  
AIRPORT NAME:  
KERRVILLE MUNI/LOUIS SCHREINER FIELD

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 12, AMDT 1  
5 APR 2012

SUP:  
AMDT: ORIG  
DATED: 10/27/2005

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION****DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KERV
RUNWAY	RW12
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	W12A
REFERENCE PATH IDENTIFIER (APPROACH ID)	295838.1745N
LTP/FTP LATITUDE	0990524.8555W
LTP/FTP LONGITUDE	+04579
LTP/FTP ELLIPSOIDAL HEIGHT	295740.1200N
FPAP LATITUDE	0990406.9000W
FPAP LONGITUDE	00040.0
THRESHOLD CROSSING HEIGHT (TCH)	F
TCH UNITS SELECTOR (METERS OR FEET USED)	03.00
GLIDEPATH ANGLE (GPA)	106.75
COURSE WIDTH AT THRESHOLD	1128
LENGTH OFFSET	40.0
HORIZONTAL ALERT LIMIT (HAL)	50.0
VERTICAL ALERT LIMIT (VAL)	

**CRC REMAINDER**

1B962758

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+04803
FPAP ORTHOMETRIC HEIGHT	+04803

CITY AND STATE  
KERRVILLE, TX

ELEVATION: 1617      THRE: 1576  
AIRPORT NAME:  
KERRVILLE MUNI/LOUIS SCHREINER FIELD

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 12, AMDT 1  
5 APR 2012

SUP:  
AMDT: ORIG  
DATED: 10/27/2005

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KERVK4FR12	AOBUCO	0100BUCOK4EA0EE	AR	HF		12440040	+	04000	18000			A	JS
SUSAP KERVK4FR12	R	0100BUCOK4EA0E	I	IF				04000	18000			A	JS
SUSAP KERVK4FR12	R	020LAVICK4EA1E	F	051TF		12440070	+	03300				A	JS
SUSAP KERVK4FR12	R	020LAVICK4EA2WALPV			ALNAV/VNAV	ALNAV							JS
SUSAP KERVK4FR12	R	021HALOLK4EA0E	S	031TF		12450025	V	0250002508		-300		A	JS
SUSAP KERVK4FR12	R	030RW12	K4PGOGY	M	031TF	12450028		01616		-300		A	JS
SUSAP KERVK4FR12	R	040		0	M	CA	1245	+	01826			A	JS
SUSAP KERVK4FR12	R	050DIYERK4EA0EY		DF				+	04100			A	JS
SUSAP KERVK4FR12	R	060DIYERK4EA0EE	R	HM		30460050	+	04100				A	JS

[illegible][illegible]

CITY AND STATE KERRVILLE, TX	ELEVATION: 1617 THRE: 1576 AIRPORT NAME:  KERRVILLE MUNI/LOUIS SCHREINER FIELD	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, AMDT 1  5 APR 2012	SUP:
				AMDT:      ORIG
				DATED:    10/27/2005