

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>TACAN STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23</b>										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>										
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: TIDYL/MJF 1.80 DME									
SLR VOR/DME			WOLFI/MJF 15.00 DME			275.96 / 29.03			3000		CLIMB TO 1200 THEN CLIMBING RIGHT TURN TO 3000 ON MJF TACAN R-186 TO CAJAN/MJF 15.00 DME AND HOLD.  <b>ADDITIONAL FLIGHT DATA:</b> HOLD S, RT, 006.34 INBOUND. CHART FAS OBST: 734 TOWER 330923N/0960458W. CHART 815 TOWER 331007N/0960434W. WOMDI TO RW17: 2.89/74 FAC CROSSES RWY C/L EXTENDED 3304 FROM THLD.									
BYP VORTAC (IAF)			WOLFI/MJF 15.00 DME (NOPT)			147.73 / 14.90			3000											
WOLFI/MJF 15.00 DME (IF/IAF)			WOMDI/6.00 DME			167.00 / 9.00			2200											
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. HOLD N WOLFI, RT, 167.00 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC <u>167.00</u> FAF WOMDI/6.00 DME <u>      </u> DIST FAF TO MAP <u>      </u> THLD <u>5.23</u> 4. MIN. ALT <u>WOLFI 3000, WOMDI 2200</u> 8. MSA FROM: MJF TACAN 2400, ESA W/IN 100 NM MJF TACAN 4000										MAG VAR: 5E      EPOCH YEAR: 1995										
<b>MINIMUMS</b>																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @								
CATEGORY =====>		A			B			C			D			E						
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA					
S-17	1060	1	540	1060	1	540	1060	1 1/4	540	1060	1 1/4	540	1060	1 1/4	540					
CIRCLING	1060	1 1/4	525	1060	1 1/4	525	1060	1 1/2	525	1100	2	565	1280	2 3/4	745					
<b>NOTES:</b> CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TERRELL ALTIMETER SETTING; INCREASE ALL MDA 80 FEET, INCREASE S-17 CATS C/D/E AND CIRCLING CATS C/E VISIBILITY 1/4 MILE. CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-17 CAT E VISIBILITY 1/4 MILE.																				
CITY AND STATE GREENVILLE, TX				ELEVATION: 535      THRE: 520 AIRPORT NAME:  MAJORS				FACILITY IDENTIFIER: MJF		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: TACAN RWY 17, ORIG  20 OCT 2011				SUP						
														AMDT      NONE						
														DATE						