

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE				
SEYOG (IF/IAF)	UCORU (FB)	308.54 / 6.70	1700	LPV: DA LNAV/VNAV: DA LNAV: RW31R CLIMB TO 2200 DIRECT CUDKO AND HOLD.			
UCORU (FAF)	KECET/1.60 NM TO RW31R (FB)	308.49 / 3.24					
KECET/1.60 NM TO RW31R	RW31R (MAP) (FO)	308.47 / 1.60		ADDITIONAL FLIGHT DATA: HOLD NW, RT, 128.37 INBOUND. CHART FAS OBST: 201 TOWER 285025N/0965355W DISTANCE TO THLD FROM 200 HATH: 0.46 NM. CHART VDP AT 0.95 MILES TO RW31R* *LNAV ONLY. WAAS CHANNEL # 82726 REFERENCE PATH ID: W31A LTP HAE: 4.2 M			
RW31R (MAP)	304 MSL	308.47					
304 MSL	CUDKO (FO)		2200				

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)							
2. HOLD SE SEYOG, RT, 308.54 INBOUND, 2200 FT. IN LIEU OF PT (IAF)							
3. FAC: <u>308.49</u> FAF: <u>UCORU</u> DIST FAF TO MAP: <u>4.84</u> THLD: <u>4.84</u>							
4. MIN. ALT: <u>SEYOG 2200, UCORU 1700, KECET/1.60 NM TO RW31R 660*</u>							
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>							
6. MIN GS INCPT: <u>1700</u> GS ALT AT: <u>UCORU 1700</u> OM: <u> </u> MM: <u> </u> IM: <u> </u>							
7. GS ANGLE: <u>3.00</u> TCH: <u>55.0</u> 34:1 IS CLEAR							
8. MSA FROM: <u> </u>							

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @			
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	304	3/4	200	304	3/4	200	304	3/4	200	304	3/4	200	304	3/4	200
LNAV/VNAV DA	372	7/8	268	372	7/8	268	372	7/8	268	372	7/8	268	372	7/8	268
LNAV MDA	460	1	356	460	1	356	460	1	356	460	1	356	460	1	356
CIRCLING	580	1	465	580	1	465	580	1 1/2	465	680	2	565		NA	

NOTES:
 CHART NOTE: BARO-VNAV NA WHEN USING PORT LAVACA ALTIMETER SETTING.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 43C (109F).
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PORT LAVACA ALTIMETER SETTING AND INCREASE ALL DA 52 FEET AND ALL MDA 60 FEET. INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 MILE AND LNAV CATS C/D/E VISIBILITY TO 1 1/8 MILE.
 (SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE VICTORIA, TX	ELEVATION: 115 THRE: 104	AIRPORT NAME: VICTORIA RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 31R, AMDT 1 31 MAY 2012	SUP: RNAV (GPS) RWY 308 AMDT: ORIG DATED 01/15/2009

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: DME/DME RNP-0.3 NA.

*LNAV ONLY

CHART NOTE: VDP NA WITH PORT LAVACA ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	218/30 CW 038/30 (NOPT)	SEYOG (IF/IAF) (FB)	2200
2.	038/30 CW 218/30	SEYOG (IF/IAF) (FO)	2200

QUALITY
2
CHECKED

CITY AND STATE
VICTORIA, TX

ELEVATION: 115 THRE: 104
AIRPORT NAME:
VICTORIA RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 31R, AMDT 1
31 MAY 2012

SUP: RNAV (GPS) RWY
30R
AMDT: ORIG
DATED: 01/15/2009

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KVCT
RUNWAY RW31R
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W31A
LTP/FTP LATITUDE 285048.6155N
LTP/FTP LONGITUDE 0965447.0885W
LTP/FTP ELLIPSOIDAL HEIGHT +00042
FPAP LATITUDE 285149.5000N
FPAP LONGITUDE 0965602.6800W
THRESHOLD CROSSING HEIGHT (TCH) 00055.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 0000
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 35.0

CRC REMAINDER

AF93FB5A

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K4
LTP ORTHOMETRIC HEIGHT +00315
FPAP ORTHOMETRIC HEIGHT +00315

CITY AND STATE

VICTORIA, TX

ELEVATION: 115

THRE: 104

AIRPORT NAME:

VICTORIA RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 31R, AMDT 1

31 MAY 2012

SUP: RNAV (GPS) RWY
30R

AMDT: ORIG

DATED: 01/15/2009

QUALITY
2
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
CHECKED

CITY AND STATE VICTORIA, TX	ELEVATION: 115	THRE: 104	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 31R, AMDT 1 31 MAY 2012	SUP: RNAV (GPS) RWY 30R	
	AIRPORT NAME:				AMDT:	ORIG
	VICTORIA RGNL				DATED:	01/15/2009