

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>VOR STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICE - FAR PART 97.23</b>								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: BUU VOR/DME							
TRUDO INT		BUU VOR/DME		087.56 / 5.23				2500		CLIMBING LEFT TURN TO 2500 IN BUU VOR/DME HOLDING PATTERN.  ADDITIONAL FLIGHT DATA: HOLD E, LT, 282.23 INBOUND. CHART FAS OBST: 993 BLDG 424033N/0881653W FAC CROSSES RWY C/L EXTENDED 2787 FROM THLD.							
1. PT <u>R</u> SIDE OF COURSE <u>102.23</u> OUTBOUND <u>2500</u> FT WITHIN <u>10</u> MILES OF <u>BUU VOR/DME</u> (IAF)																	
2.																	
3. FAC <u>282.23</u> FAF														DIST FAF TO MAP <u>        </u> THLD <u>        </u>			
4. MIN. ALT <u>WEDIN/2.60 DME 1460*</u>																	
8. MSA FROM: <u>BUU VOR/DME 2700</u>														MAG VAR: 1W      EPOCH YEAR: 1985			
<b>MINIMUMS</b>																	
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: NA		STANDARD @					
CATEGORY >>>>>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-29	1460	1	681	1460	1	681	1460	2	681	1460	2 1/4	681					
CIRCLING	1460	1	681	1460	1	681	1460	2	681	1460	2 1/4	681					
<b>WEDIN FIX MINIMUMS</b>																	
S-29	1300	1	521	1300	1	521	1300	1 1/2	521	1300	1 3/4	521					
CIRCLING	1340	1	561	1360	1	581	1360	1 1/2	581	1380	2	601					
NOTES: CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. *1540 WHEN USING GENERAL MITCHELL INTERNATIONAL ALTIMETER SETTING CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GENERAL MITCHELL INTERNATIONAL ALTIMETER SETTING AND INCREASE ALL MDAS 80 FEET, AND INCREASE S-29 AND CIRCLING CATS B, C, AND D SEE 8260-10																	
CITY AND STATE				ELEVATION: 779    TDZE: 779				FACILITY IDENTIFIER:				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP VOR OR GPS RWY	
BURLINGTON, WI				AIRPORT NAME:				BUU				VOR RWY 29, AMDT 8				29	
				BURLINGTON MUNI								APR 10 2008				AMDT 7	
																DATE 01/23/2003	

VOR STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## NOTES CONT.

VISIBILITIES 1/4 MILE, AND WEDIN FIX MINIMUMS S-29 AND CIRCLING CATS C AND D VISIBILITIES 1/4 MILE.

CITY AND STATE

BURLINGTON, WI

ELEVATION: 779 TDZE: 779

AIRPORT NAME:

BURLINGTON MUNI

FACILITY  
IDENTIFIER:

BUU

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 29, AMDT 8

APR 10 2008

SUP: VOR OR GPS RWY  
29

AMDT: 7

DATED: 01/23/2003