

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW36 LNAV: RW36 CLIMBING RIGHT TURN TO 3500 DIRECT DLL VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 281.00 INBOUND. CHART FAS OBST: 1266 TREE 433006N/0895840W 1659 AAO 432615N/0895838W WAAS CHANNEL # 82727 REFERENCE PATH ID: W36A CUKON TO RW36: 3.00/50. CHART BARABOO AWOS. LTP HAE: 233.7 M											
LNR VOR/DME (IAF)	WURVI (FB)	069.20 / 6.96	3500												
NEGUS (IAF)	WURVI (FB)	310.92 / 8.94	3500												
WURVI (IF)	CUKON (FB)	000.49 / 6.10	2500												
CUKON (FAF)	FETAD/2.80 NM TO RW36 (FB)	000.49 / 2.13													
FETAD/2.80 NM TO RW36	RW36 (MAP) (FO)	000.49 / 2.80													
RW36 (MAP)	1306 MSL	000.49													
1306 MSL	DLL VORTAC (FO)		3500												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT WURVI 3. FAC: <u>000.49</u> FAF: <u>CUKON</u> DIST FAF TO MAP: <u>4.93</u> THLD: <u>4.93</u> 4. MIN. ALT: <u>WURVI 3500, CUKON 2500, FETAD/2.80 NM TO RW36 1800</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u> </u> 34:1 IS NOT CLEAR 8. MSA FROM: <u>RW36 3300</u>				MAG VAR: 0E EPOCH YEAR: 1985											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A X															
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	1560	1	679	1560	1	679		NA			NA				
LNAV MDA	1580	1	699	1580	1	699		NA			NA				
CIRCLING	1600	1	694	1600	1	694		NA			NA				
NOTES: CHART NOTE: USE BARABOO ALTIMETER SETTING; WHEN NOT RECEIVED, USE LONE ROCK ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, INCREASE LNAV AND CIRCLING CAT B VISIBILITY TO 1 1/4. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. (SEE FORM 8260-10)															
CITY AND STATE REEDSBURG, WI		ELEVATION: 906 THRE: 881 AIRPORT NAME: REEDSBURG MUNI		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 05 APR 2012				SUP: AMDT: NONE DATED					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON LNR VOR/DME AIRWAY RADIALS 104 CW 147.

QUALITY
CHECKED

CITY AND STATE REEDSBURG, WI	ELEVATION: 906	THRE: 881	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 05 APR 2012	SUP:
	AIRPORT NAME:				AMDT: NONE
	REEDSBURG MUNI				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	C35
RUNWAY	RW36
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W36A
LTP/FTP LATITUDE	433109.5586N
LTP/FTP LONGITUDE	0895856.4145W
LTP/FTP ELLIPSOIDAL HEIGHT	+02337
FPAP LATITUDE	433238.6700N
FPAP LONGITUDE	0895855.3600W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1368
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

CRC REMAINDER

CC1B668D

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+02687
FPAP ORTHOMETRIC HEIGHT	+02687

QUALITY
CHECKED

CITY AND STATE

REEDSBURG, WI

ELEVATION: 906

THRE: 881

AIRPORT NAME:

REEDSBURG MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 36, ORIG

05 APR 2012

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

CITY AND STATE REEDSBURG, WI	ELEVATION: 906 THRE: 881 AIRPORT NAME: REEDSBURG MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 05 APR 2012	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
PP	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP C35 K5PR36 RW36 001 0000W36A0N4331095585W08958564145+023370300N4332386700W08958553600106751368000500F400000CC1B668D												
	SUSAP C35 K5PR36 RW36 002E +02687+02687LP 82727												

	1	2	3	4	5	6	7	8	9	0	1	2	3
MSA	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP C35 K5SRW36 K5PG 0 18018003325 M												

CITY AND STATE

REEDSBURG, WI

ELEVATION: 906

THRE: 881

AIRPORT NAME:

REEDSBURG MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 36, ORIG

05 APR 2012

SUP:

AMDT: NONE

DATED: