

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>LOC STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25</b>								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>							
FROM		TC		COURSE AND DISTANCE				ALTITUDE		<b>MAP: 5.60 MILES AFTER FAHEY/PXY 7.14 DME/RADAR OR AT I-PXY 1.54 DME FIX</b>  <b>CLIMB TO 2800 THEN RIGHT TURN DIRECT BAE VORTAC AND HOLD, OR AS DIRECTED BY ATC.</b>  <b>ALTERNATE MA: CLIMB TO 2800 THEN CLIMBING RIGHT TURN TO 3000 DIRECT LJT VOR/DME AND ON LJT VOR/DME R-086 TO PROOT INT AND HOLD.</b>  <b>ADDITIONAL FLIGHT DATA:</b> HOLD W, RT, 090.00 INBOUND. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD N PROOT INT, RT, 172.46 INBOUND. CHART FAS OBST: 891 STACK 425721N/0875146W CHART VDP AT 2.93 DME; DISTANCE VDP TO THLD 1.39 MILES. CHART IN PLANVIEW: PROOT INT. FAHEY TO RW25L: 3.00/47.							
CITKI/I-PXY 13.99 DME/RADAR (IF/IAF)		FAHEY/I-PXY 7.14 DME/RADAR		253.66 / 6.85 (I-PXY)				2500									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT CITKI 3. FAC 253.66 FAF FAHEY/I-PXY 7.14 DME/RADAR DIST FAF TO MAP 5.60 THLD 5.60 4. MIN. ALT CITKI 2900, FAHEY 2500 8. MSA FROM: BAE VORTAC 2900														MAG VAR: 2W		EPOCH YEAR: 1995	
<b>MINIMUMS</b>																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: NA		<b>STANDARD</b>					
CATEGORY =====>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-25L	1160	1	490	1160	1	490	1160	1 3/8	490	1160	1 3/8	490					
CIRCLING	1240	1	511	1240	1	511	1240	1 1/2	511	1280	2	551					
NOTES:  CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: RADAR REQUIRED.																	
CITY AND STATE				ELEVATION: 729      THRE: 670				FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP			
MILWAUKEE, WI				AIRPORT NAME:				I-PXY		LOC RWY 25L, AMDT 5				AMDT 4A			
				GENERAL MITCHELL INTL						20 OCT 2011				DATE 06/22/1995			

QUALITY  
CHECKED

**LOC STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE

MILWAUKEE, WI

ELEVATION: 729

THRE: 670

AIRPORT NAME:

GENERAL MITCHELL INTL

FACILITY  
IDENTIFIER:

I-PXY

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

LOC RWY 25L, AMDT 5

20 OCT 2011

SUP:

AMDT: 4A

DATED: 06/22/1995

## FLIGHT STANDARDS SERVICES - FAR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibility which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	<b>4A</b>
DATED:	<b>06/22/1995</b>

## U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

## LOC STANDARD INSTRUMENT APPROACH PROCEDURE

## FLIGHT STANDARDS SERVICES - FAR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - LOC

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		CITKI	010	FACF	IF		FB				AA 02900	
		FAHEY	020	FAF	CF		FB		254.0 ( )	006.9	AA 02500	
		RW25L	030	MAP	CF		FO		254.0 ( )	005.6	AT 00717	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		253.7 ( )		AA 02800	
		BAE	050		DF		FO				AA 02800	
		BAE	060		HM	R	FO		090.0 ( )	T01.0	AA 02800	
POINT DATA		WAYPOINT		LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS		
		BAE		N430700.67		W0881703.65		N4307.011		W08817.061		
		IPXY (DME)		N425618.49		W0875523.67		N4256.308		W08755.395		
		CITKI		N430039.09		W0873717.10		N4300.652		W08737.285		
		FAHEY		N425830.64		W0874609.10		N4258.511		W08746.152		
		RW25L		N425645.12		W0875323.54		N4256.752		W08753.392		
		IPXY (LOC)		N425616.06		W0875522.76		N4256.268		W08755.379		
RUNWAY DATA				THRESHOLD								
		RWY		ELEVATION		TCH						
		RW25L	00670			47						

CITY AND STATE  
MILWAUKEE, WI

ELEVATION: 729      THRE: 670  
AIRPORT NAME:  
GENERAL MITCHELL INTL

FACILITY  
IDENTIFIER:  
I-PXY

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:  
LOC RWY 25L, AMDT 5  
20 OCT 2011

SUP:  
AMDT: 4A  
DATED: 06/22/1995