

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION LDA STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 3.36 NM AFTER KANAN LOM OR AT CCR 3.15 DME					
COLLI INT		KANAN LOM		359.21 / 11.25				5300		CLIMBING RIGHT TURN TO 3000 DIRECT CCR VOR/DME THEN ON CCR VOR/DME R-043.64 TO REJOY INT/CCR 14.89 DME AND HOLD. *MISSED APPROACH REQUIRES MINIMUM CLIMB OF 282 FEET PER NM TO 1800. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 223.64 INBOUND. CHART FAS OBST: 319 TREE 380207N/1220132W CHART 2800 PRIOR TO KANAN LOM IN PROFILE. CHART CIRCLING ICON. KANAN LOM TO RW19R: 3.47/40. CHART IN PLANVIEW: ADF OR DME OR RADAR REQUIRED. CHART PLANVIEW NOTE: LOC OFFSET 5.76 DEGREES.					
REJOY INT/CCR 14.89 DME (IAF)		JOANS INT/SGD 18.47 DME (NOPT)		254.37 / 10.04 (SGD R-074)				2000							
JOANS INT/CCR 8.13 DME (IF)		ZUKOP INT/CCR 4.28 DME		184.76 / 3.86 (I-CCR)				1500							
ZUKOP INT/CCR 4.28 DME		KANAN LOM		184.76 / 4.00 (I-CCR)				1300							
1. PT <u> R </u> SIDE OF COURSE <u> 004.76 </u> OUTBOUND <u> 2600 </u> FT WITHIN <u> 10 </u> MILES OF <u> KANAN LOM </u> (IAF) 2. _____ 3. FAC <u> 184.76 </u> FAF <u> KANAN LOM </u> DIST FAF TO MAP <u> 3.36 </u> THLD <u> 3.36 </u> 4. MIN. ALT <u> ZUKOP 1500, KANAN LOM 1300 </u> 8. MSA FROM: <u> CCR VOR/DME 360-090 3100, 090-180 5100, 180-360 4100 </u>										MAG VAR: 13E		EPOCH YEAR: 2020			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-19R*	440	3/4	418	440	3/4	418	440	1	418	440	1	418			
S-19R	780	3/4	758	780	1	758	780	1 7/8	758	780	1 7/8	758			
CIRCLING	780	1	754	780	1 1/4	754	960	2 3/4	934	1300	3	1274			
NOTES: CHART NOTE: CIRCLING NA W OF RWY 1L-19R. CHART NOTE: CIRCLING RWY 1L, 32R NA AT NIGHT. CHART NOTE: RWY 19R HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME REQUIRED. (CONTINUED ON PAGE 2)															
CITY AND STATE CONCORD, CA		ELEVATION: 26 AIRPORT NAME: BUCHANAN FIELD		TDZE: 22		FACILITY IDENTIFIER: I-CCR		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LDA RWY 19R, AMDT 8 22 JUNE 2017				SUP			
												AMDT 7E			
												DATE 09/15/2016			

QUALITY
 33
 CHECKED

**LDA STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT COLLI ON V6 SOUTHBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT REJOY ON V6 NORTHBOUND.

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).

CHART NOTE: *FOR INOPERATIVE ALS, INCREASE S-19R CATS C/D VISIBILITY TO 1 1/8 SM.

CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-19R CATS C/D VISIBILITY TO 2 SM.

QUALITY
33
CHECKED

CITY AND STATE

CONCORD, CA

ELEVATION: 26

TDZE: 22

AIRPORT NAME:

BUCHANAN FIELD

FACILITY
IDENTIFIER:
I-CCR

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

LDA RWY 19R, AMDT 8

22 JUNE 2017

SUP:

AMDT: 7E

DATED: 09/15/2016

**LDA STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE

CONCORD, CA**ELEVATION: 26****TDZE: 22**

AIRPORT NAME:

BUCHANAN FIELDFACILITY
IDENTIFIER:
I-CCR

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

LDA RWY 19R, AMDT 8

22 JUNE 2017

SUP:

AMDT: **7E**DATED: **09/15/2016**